

# Bellow gripper DHEB-14-E-D-E-P

Part number: 1320790

FESTO



 General operating condition

## Data sheet

| Feature                                      | Value                                                                                      |
|----------------------------------------------|--------------------------------------------------------------------------------------------|
| Size                                         | 14                                                                                         |
| Stroke of bellows                            | 7 mm                                                                                       |
| Min. $\varnothing$ to be gripped             | 15 mm                                                                                      |
| Max. $\varnothing$ to be gripped             | 19.5 mm                                                                                    |
| Mounting position                            | Any                                                                                        |
| Mode of operation                            | Single-acting<br>Closed                                                                    |
| Gripper function                             | Adaptive                                                                                   |
| Design                                       | Contracting diaphragm<br>Force pilot operated motion sequence                              |
| Guide                                        | Basic Guide                                                                                |
| Position detection                           | None                                                                                       |
| Operating pressure                           | 5 bar ... 8 bar                                                                            |
| Reset pressure                               | <1 bar                                                                                     |
| Max. operating frequency of gripper          | $\leq 4$ Hz                                                                                |
| Min. opening time at 0.6 MPa (6 bar, 87 psi) | 20 ms                                                                                      |
| Min. closing time at 0.6 MPa (6 bar, 87 psi) | 40 ms                                                                                      |
| Operating medium                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC               | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                       | VDMA24364 zone III                                                                         |
| Ambient temperature                          | 5 °C ... 60 °C                                                                             |
| Average replacement interval for the bellows | 0.5 MioCyc                                                                                 |
| Guide value for effective load               | 0.15 kg                                                                                    |
| Product weight                               | 17 g                                                                                       |
| Type of mounting                             | With male thread<br>Via lock nut                                                           |
| Pneumatic connection                         | M3                                                                                         |
| Note on materials                            | RoHS compliant                                                                             |
| Material bellows                             | EPDM                                                                                       |
| Material housing                             | Aluminium<br>anodised                                                                      |