

# Blanking plug NPQP-P-S10-FD-P10

Part number: 133131

FESTO



 General operating condition

## Data sheet

| Feature                                       | Value                                    |
|---|--|
| Size  | Standard                                 |
| Design  | Blanking plug                            |
| Size of pack                                  | 10                                       |
| Design  | Push-pull principle                      |
| Operating pressure complete temperature range | -0.095 MPa ... 0.45 MPa                  |
| Operating pressure complete temperature range | -0.95 bar ... 4.5 bar                    |
| Operating pressure complete temperature range | -13.775 psi ... 65.25 psi                |
| Temperature-dependent operating pressure      | -0.095 MPa ... 1 MPa                     |
| Temperature-dependent operating pressure      | -0.95 bar ... 10 bar                     |
| Temperature-dependent operating pressure      | -13.775 psi ... 145 psi                  |
| Operating medium                              | Compressed air to ISO 8573-1:2010 [7::-] |
| Note on operating and pilot medium            | Lubricated operation possible            |
| Corrosion resistance class CRC                | 4 - Very high corrosion stress           |
| LABS (PWIS) conformity                        | VDMA24364 zone III                       |
| Suitable for use with food                    | See supplementary material information   |
| Ambient temperature                           | -20 °C ... 60 °C                         |
| Product weight                                | 2 g                                      |
| Pneumatic connection, port 1                  | Push-in sleeve Ø 10 mm                   |
| Note on materials                             | RoHS compliant                           |
| Material housing                              | PP                                       |
| Material tubing clamp component               | High-alloy stainless steel               |