

Solenoid valve

VZWP-L-M22C-G1-250-3AP4-40

Part number: 1489964

FESTO



 General operating condition

Data sheet

| Feature | Value |
|----------------------------------|--|
| Design | Piloted piston poppet valve |
| Type of actuation | Electrical |
| Sealing principle | Soft |
| Mounting position | Coil on top (preferred) |
| Type of mounting | Inline installation |
| Connection Process valve | G1 |
| Electrical connection | Plug To EN 175301-803 Square design |
| Nominal size | 25 mm |
| Valve function | 2/2-way, single solenoid, closed |
| Manual override | None |
| Flow direction | Non-reversible |
| Medium | Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases Neutral fluids Other media on request |
| Nominal pressure PN | 40 |
| Pressure difference | 0.05 MPa |
| Pressure difference | 0.5 bar |
| Pressure difference | 7.25 psi |
| Characteristic coil data | 230 V AC: 50/60 Hz, pick-up power 10.5 VA, holding power 7.6 VA |
| Insulation material class | H |
| Permissible voltage fluctuations | +/-10% |
| Duty cycle | 100% |
| Type of piloting | Piloted |
| Symbol | 00992974 |
| Medium pressure | 0.05 MPa ... 4 MPa |
| Medium pressure | 0.5 bar ... 40 bar |
| Medium pressure | 7.25 psi ... 580 psi |
| Max. viscosity | 22 mm ² /s |

| Feature | Value |
|---|--|
| Media temperature | -10 °C ... 80 °C |
| Ambient temperature | -10 °C ... 35 °C |
| Leakage rate to EN 12266-1 | A |
| Flow rate Kv | 11.5 m³/h |
| Standard nominal flow rate (standardised to DIN 1343) | 12250 l/min |
| Switching time on | 130 ms |
| Switching time off | 300 ms |
| Note on materials | RoHS compliant |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Material housing | Cast brass |
| Material number housing | CW617N |
| Material seals | NBR |
| Material screws | High-alloy stainless steel |
| Material number screw | 1,4301 |
| Product weight | 1400 g |
| CE mark (see declaration of conformity) | To EU Low Voltage Directive |
| UKCA marking (see declaration of conformity) | To UK regulations for electrical equipment |
| Degree of protection | IP65 |
| Corrosion resistance class CRC | 1 - Low corrosion stress |