

Solenoid valve

VZWF-L-M22C-N112-400-1P4-10-R1

FESTO

Part number: 1492172



[PDF](#) General operating condition

Data sheet

| Feature | Value |
|----------------------------------|--|
| Design | Diaphragm valve Force pilot operated |
| Type of actuation | Electrical |
| Sealing principle | Soft |
| Mounting position | Magnet upright |
| Type of mounting | Inline installation |
| Connection Process valve | 1 1/2 NPT |
| Electrical connection | Plug To EN 175301-803 Square design |
| Nominal size | 40 mm |
| Valve function | 2/2-way, single solenoid, closed |
| Manual override | None |
| Flow direction | Non-reversible |
| Medium | Compressed air to ISO 8573-1:2010 [7:-:-] Inert gases Mineral oil Water Neutral fluids Other media on request |
| Nominal pressure PN | 40 |
| Pressure difference | 0 MPa |
| Pressure difference | 0 bar |
| Pressure difference | 0 psi |
| Characteristic coil data | 24 V DC: 30.0 W |
| Permissible voltage fluctuations | +/-10% |
| Symbol | 00992976 |
| Medium pressure | 0 MPa ... 1 MPa |
| Medium pressure | 0 bar ... 10 bar |
| Medium pressure | 0 psi ... 145 psi |
| Max. viscosity | 22 mm ² /s |
| Media temperature | -10 °C ... 80 °C |

| Feature | Value |
|---|--|
| Ambient temperature | -10 °C ... 35 °C |
| Leakage rate to EN 12266-1 | A |
| Flow rate Kv | 22.5 m³/h |
| Standard nominal flow rate (standardised to DIN 1343) | 23500 l/min |
| Switching time on | 620 ms |
| Switching time off | 1140 ms |
| Note on materials | RoHS compliant |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Material housing | Cast stainless steel |
| Material number housing | 1,4581 |
| Material seals | NBR |
| Material screws | High-alloy stainless steel |
| Material number screw | 1,4301 |
| Product weight | 4500 g |
| CE mark (see declaration of conformity) | In accordance with EU Pressure Equipment Directive |
| Degree of protection | IP65 |
| Corrosion resistance class CRC | 3 - high corrosion stress |