



Flat cylinder DZH-50- -PPV-A-S2

Part number: 151774

FESTO



General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

| Feature | Value |
|--|--|
| Stroke | 1 mm ... 1000 mm |
| Piston diameter | 50 mm Equivalent diameter |
| Piston rod thread | M16x1.5 |
| Torsional backlash at piston rod +/- | 0.75 deg |
| Cushioning | Pneumatic cushioning, adjustable at both ends |
| Mounting position | Any |
| Mode of operation | Double-acting |
| Design | Piston Piston rod Profile barrel |
| Position detection | Via proximity switch |
| Symbol | 00991237 |
| Variants | Through piston rod |
| Protection against torque/guide | Oval piston |
| Operating pressure | 0.06 MPa ... 1 MPa |
| Operating pressure | 0.6 bar ... 10 bar |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Ambient temperature | -20 °C ... 80 °C |
| Cushioning length | 23 mm |
| Max. torque for protection against torsion | 1.7 Nm |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke | 989 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 989 N |
| Moving mass for 0 mm stroke | 626 g |
| Additional moving mass per 10 mm stroke | 48.2 g |
| Additional weight per 10 mm stroke | 76.5 g |
| Basic weight for 0 mm stroke | 1474 g |
| Type of mounting | With female thread With accessories |
| Pneumatic connection | G1/4 |
| Note on materials | RoHS compliant |
| Material cover | Aluminium |

| Feature | Value |
|----------------------|------------------|
| Material seals | TPE-U(PU) |
| Material housing | Aluminium |
| Material piston seal | TPE-U(PU) |
| Material piston rod | High-alloy steel |