

# Plug socket with cable KMEB-2-230-2,5

Part number: 174846

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                      | Value                                                                 |
|----------------------------------------------|-----------------------------------------------------------------------|
| Type of mounting                             | On solenoid valve via M2.5 central screw                              |
| Mounting position                            | Any                                                                   |
| Product weight                               | 200 g                                                                 |
| Electrical connection                        | 4-pin<br>Angled socket<br>Type C<br>To DIN EN 175301-803              |
| Nominal operating voltage AC                 | 230 V                                                                 |
| Protective conductor connection              | Available                                                             |
| Cable length                                 | 2.5 m                                                                 |
| Cable diameter                               | 6.2 mm                                                                |
| Cable structure                              | 3 x 0.75 mm <sup>2</sup>                                              |
| Degree of protection                         | IP65<br>To IEC 60529                                                  |
| Ambient temperature                          | -20 °C ... 80 °C                                                      |
| CE mark (see declaration of conformity)      | To EU Low Voltage Directive<br>In accordance with EU RoHS Directive   |
| UKCA marking (see declaration of conformity) | To UK RoHS instructions<br>To UK regulations for electrical equipment |
| LABS (PWIS) conformity                       | VDMA24364-B2-L                                                        |
| Note on materials                            | RoHS compliant                                                        |
| Material cable sheath                        | TPE-U(PUR)                                                            |
| Material housing                             | Process automation<br>POM                                             |
| Material electrical contact                  | Bronze                                                                |