

Manual override HAB-3/8

Part number: 184587

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|--|--|
| Nominal size | 11 mm |
| Mounting position | Any |
| Valve function | Exhaust component |
| Operating pressure | 0 bar ... 10 bar |
| Standard nominal flow rate, exhaust 0.6-0.5 MPa (6-5 bar, 87-72.5 psi) | 165 l/min |
| Explosion protection | Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Media temperature | -20 °C ... 80 °C |
| Ambient temperature | -20 °C ... 80 °C |
| Max. tightening torque | 35 Nm |
| Type of mounting | Screw-in |
| Pneumatic connection, port 1 | G3/8 |
| Pneumatic connection, port 2 | G3/8 |
| Note on materials | RoHS compliant |
| Material housing | Anodised wrought aluminium alloy |