

Suction cup with connection ESS-60-SN

Part number: 189314

FESTO



[PDF](#) General operating condition

Data sheet

| Feature | Value |
|---|---|
| Min. workpiece radius | 350 mm |
| Nominal size | 6 mm |
| Suction cup diameter | 60 mm |
| Suction cup volume | 3.953 cm ³ |
| Position of connection | On top |
| Mounting position | Any |
| Symbol | 00991485 |
| Correlation to suction-cup holder | Size 5 |
| Suction cup shape | Round, flat |
| Operating pressure | -0.095 MPa ... 0 MPa |
| Operating pressure | -0.95 bar ... 0 bar |
| Operating pressure | -13.775 psi ... 0 psi |
| Nominal operating pressure | -0.07 MPa |
| Nominal operating pressure | -0.7 bar |
| Nominal operating pressure | -10.15 psi |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7::-] |
| Corrosion resistance class CRC | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-A1-L |
| Suitable for use with food | See supplementary material information |
| Ambient temperature | -10 °C ... 70 °C |
| Holding force at nominal operating pressure | 166.1 N |
| Lateral force at nominal operating pressure | 136 N |
| Product weight | 49 g |
| Type of mounting | Via vacuum port |
| Vacuum connection | M10 |
| Colour | Black |
| Shore hardness | 60 +/-5 |
| Material screwed plug | Nickel-plated wrought aluminium alloy Nickel-plated steel Steel, galvanised and chrome-plated |
| Note on materials | RoHS compliant |

| Feature | Value |
|----------------------|-------|
| Material suction cup | NBR |