



PRODUCT-DETAILS

AF96-30-00-12
AF96-30-00-12 48-130V50/60HZ-DC
Contactors



General Information	
Extended Product Type	AF96-30-00-12
Product ID	1SBL407001R1200
EAN	3471523133228
Catalog Description	AF96-30-00-12 48-130V50/60HZ-DC Contactors
Long Description	The AF96-30-00-12 is a 3 pole - 1000 V IEC or 600 UL contactor with screw terminals, controlling motors up to 45 kW / 400 V AC (AC-3) or 60 hp / 480 V UL and switching power circuits up to 130 A (AC-1) or 115 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100214C0202
Instructions and Manuals	1SBC101036M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	70 mm
Product Net Depth / Length	116 mm
Product Net Height	125.5 mm
Product Net Weight	1.22 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Number of Poles	3P
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-1:22, CSA C22.2 No. 60947-4-1:22
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 130 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 130 A (690 V) 60 °C 105 A (690 V) 70 °C 90 A
Rated Operational Current AC-3 (I _e)	(415 V) 60 °C 96 A (440 V) 60 °C 96 A (500 V) 60 °C 80 A (690 V) 60 °C 57 A (1000 V) 60 °C 30 A (380 / 400 V) 60 °C 105 A (220 / 230 / 240 V) 60 °C 105 A
Rated Operational Current AC-3e (I _e)	(415 V) 60 °C 96 A (440 V) 60 °C 96 A (500 V) 60 °C 80 A (690 V) 60 °C 57 A (380 / 400 V) 60 °C 105 A (220 / 230 / 240 V) 60 °C 105 A
Rated Operational Current DC-1 (I _e)	(110 V) 2 Poles in Series, 40 °C 130 A (110 V) 2 Poles in Series, 60 °C 105 A (110 V) 2 Poles in Series, 70 °C 90 A (110 V) 3 Poles in Series, 40 °C 130 A (110 V) 3 Poles in Series, 60 °C 105 A (110 V) 3 Poles in Series, 70 °C 90 A

	(220 V) 3 Poles in Series, 40 °C 125 A (220 V) 3 Poles in Series, 60 °C 105 A (220 V) 3 Poles in Series, 70 °C 90 A (72 V) 1-Pole, 40 °C 130 A (72 V) 1-Pole, 60 °C 105 A (72 V) 1-Pole, 70 °C 90 A (72 V) 2 Poles in Series, 40 °C 130 A (72 V) 2 Poles in Series, 60 °C 105 A (72 V) 2 Poles in Series, 70 °C 90 A (72 V) 3 Poles in Series, 40 °C 130 A (72 V) 3 Poles in Series, 60 °C 105 A (72 V) 3 Poles in Series, 70 °C 90 A
Rated Operational Current DC-3 (I _e)	(110 V) 2 Poles in Series, 40 °C 130 A (110 V) 2 Poles in Series, 60 °C 105 A (110 V) 2 Poles in Series, 70 °C 90 A (110 V) 3 Poles in Series, 40 °C 130 A (110 V) 3 Poles in Series, 60 °C 105 A (110 V) 3 Poles in Series, 70 °C 90 A (220 V) 3 Poles in Series, 40 °C 130 A (220 V) 3 Poles in Series, 60 °C 105 A (220 V) 3 Poles in Series, 70 °C 90 A (72 V) 1-Pole, 40 °C 130 A (72 V) 1-Pole, 60 °C 105 A (72 V) 1-Pole, 70 °C 90 A (72 V) 2 Poles in Series, 40 °C 130 A (72 V) 2 Poles in Series, 60 °C 105 A (72 V) 2 Poles in Series, 70 °C 90 A (72 V) 3 Poles in Series, 40 °C 130 A (72 V) 3 Poles in Series, 60 °C 105 A (72 V) 3 Poles in Series, 70 °C 90 A
Rated Operational Current DC-5 (I _e)	(110 V) 2 Poles in Series, 40 °C 130 A (110 V) 2 Poles in Series, 60 °C 105 A (110 V) 2 Poles in Series, 70 °C 90 A (110 V) 3 Poles in Series, 40 °C 130 A (110 V) 3 Poles in Series, 60 °C 105 A (110 V) 3 Poles in Series, 70 °C 90 A (220 V) 3 Poles in Series, 40 °C 130 A (220 V) 3 Poles in Series, 60 °C 105 A (220 V) 3 Poles in Series, 70 °C 90 A (72 V) 1-Pole, 40 °C 130 A (72 V) 1-Pole, 60 °C 105 A (72 V) 1-Pole, 70 °C 90 A (72 V) 2 Poles in Series, 40 °C 130 A (72 V) 2 Poles in Series, 60 °C 105 A (72 V) 2 Poles in Series, 70 °C 90 A (72 V) 3 Poles in Series, 40 °C 130 A (72 V) 3 Poles in Series, 60 °C 105 A (72 V) 3 Poles in Series, 70 °C 90 A
Rated Operational Power AC-3 (P _e)	(415 V) 55 kW (440 V) 55 kW (500 V) 55 kW (690 V) 55 kW (1000 V) 40 kW (380 / 400 V) 45 kW (380 / 400 V) 55 kW (220 / 230 / 240 V) 25 kW (220 / 230 / 240 V) 30 kW
Rated Operational Power AC-3e (P _e)	(415 V) 55 kW (440 V) 55 kW (500 V) 55 kW (690 V) 55 kW (380 / 400 V) 45 kW (380 / 400 V) 55 kW (220 / 230 / 240 V) 25 kW (220 / 230 / 240 V) 30 kW
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 840 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 140 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1200 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 450 A

Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 1150 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 750 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
Coil Consumption	Average Holding Value 50 / 60 Hz 4 V-A Average Holding Value 50 Hz 4 V-A Average Holding Value 60 Hz 4 V-A Average Holding Value DC 2 W Average Holding Value, from Warm State 2 W
Power Loss	at Rated Operating Conditions AC-1 per Pole 8.2 W at Rated Operating Conditions AC-3 per Pole 4.5 W
Operate Time	Between Coil De-energization and NC Contact Closing 19 ... 105 ms Between Coil De-energization and NO Contact Opening 17 ... 100 ms Between Coil Energization and NC Contact Opening 38 ... 95 ms Between Coil Energization and NO Contact Closing 42 ... 100 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 or 2 x M6 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 6 ... 50 mm ² Flexible with Insulated Ferrule 1/2x 6 ... 50 mm ² Rigid Stranded 1x 6 ... 70 mm ² Rigid Stranded 2x 6 ... 50 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Control Circuit 10 mm Main Circuit 17 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Recommended Screw Driver	Pozidriv PZ
Tightening Torque	Control Circuit 1.2 N-m Main Circuit 6 N-m
Terminal Type	Screw Terminals
Product Name	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 115 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 7-1/2 hp (200 ... 208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 40 hp (240 V AC) Single Phase 20 hp (440 ... 480 V AC) Three Phase 75 hp (550 ... 600 V AC) Three Phase 75 hp
Connecting Capacity	Rigid Stranded 1/2x 6-1 AWG

Main Circuit UL/CSA	
Connecting Capacity	Rigid Solid 1/2x 18-14 AWG
Control Circuit UL/CSA	Rigid Stranded 1/2x 18-14 AWG
Tightening Torque	Control Circuit 11 in-lb
UL/CSA	Main Circuit 53 in-lb
Full Load Amps Motor Use	(120 V AC) Single Phase 80 A (200 ... 208 V AC) Three Phase 92 A (220 ... 240 V AC) Three Phase 80 A (240 V AC) Single Phase 88 A (440 ... 480 V AC) Three Phase 77 A (550 ... 600 V AC) Three Phase 77 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -40 ... 70 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: A 25 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g Open, Shock Direction: B1 5 g
Resistance to Vibrations	3g Closed Position & 3g Open Position 5 ... 300 Hz
Pollution Degree	3

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	733a5606-6a85-4acd-b062-78b76c3c365e China
Simplified SCIP	eb6eb713-2a62-453b-92aa-760d6a4462d9 Croatia 9ff14233-c8b7-46ec-9412-529758bb10a6 Belgium 3e8c126a-fde6-4c8b-aeae-dbf34c0bd9c9 Hungary 79ab534d-c20a-4979-8538-8cae1b029a4e Norway 776ba020-1a77-451e-81a0-9b7ce476caf3 Estonia 808057af-e766-424d-bbc4-c64d21dc2e2a Bulgaria 6daa4191-5a6c-4903-a3af-fc7374259305 Finland 21c03b39-b021-422e-87fc-582d4d2e1b3a Belgium aa5973cf-96f9-4d98-b73d-e9327079fd4c Greece 0b8575de-8866-4635-990b-bf2c0aa905f1 Germany e9424cb5-b221-4569-ae09-abf576f50261 Portugal 38f47775-eb48-471a-9ad6-1422bc6bad1f Hungary 0050f508-7db9-4e90-b2f5-2315b8a24c77 Netherlands 82e36a60-fec0-4d7f-a1f9-64db541e0e82 Germany 26a2945c-a33f-46fd-b260-4a2de59db99e Poland 04d882df-0d42-47a6-ab1a-8d05ab68ed8a Poland c1bd577d-e86c-401e-8820-43cfa72a7595 France f71a032e-6359-4e07-8bbf-15d48c509cb3 Sweden d21621b3-3355-4b05-96f6-0c1aef115d36 France 06f379d9-ab22-465e-be68-2e8ff406460d Germany bde53dc9-2b00-4ce6-ab13-92935036313c Germany 2aa16854-f956-4b56-8f21-114353b26141 Poland 82987081-30c3-4bd1-b52a-3e117d320172 Sweden 53c29af4-cec8-4f5c-9203-620b80a90893 Germany 05805160-cfa8-461a-af85-a324590aaf24 Denmark

8cea6012-3220-49a1-9b78-a11a4d39f8cb Spain
7eafd1b6-88e4-48e2-8467-44a516dc35ab Czech Republic

Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions	Yes
End Of Life Disassembling Instructions	1SBC101081M6801
Environmental Product Declaration - EPD	2TFP200017A1001 1SBD250584E2000
Sustainable Material Content in Packaging (wt. %)	FSC Recycled Paper - 94.6 %
Sustainable Material Content in Product (wt. %)	Recycled Metal - 28.2 %

Certificates and Declarations

A2L Certificate – UL	9AKK108469A4890 9AKK108469A4892
ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H36994B1
CB Certificate	CB_SE-113142A1
CCC Certificate	CQC_2013010304646569
Declaration of Conformity - CCC	2020980304001255
Declaration of Conformity - CE	1SBD250000U1000
Declaration of Conformity - UKCA	1SBD250031U1000
DNV Certificate	DNV_TAE00001AF-4
KC Certificate	KC_HW02016-15011C
LR Certificate	LRS_LR23403517TA-02
RINA Certificate	RINA_ELE084013XG
RMRS Certificate	RMRS_1802705280
UL Certificate	UL-US-L312527-1141-10303102-9 UL-CA-L312527-4141-10303102-9
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	150 mm
Package Level 1 Depth / Length	150 mm
Package Level 1 Height	103 mm
Package Level 1 Gross Weight	1.34 kg
Package Level 1 EAN	3471523133228
Package Level 2 Units	box 8 piece

Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	300 mm
Package Level 2 Gross Weight	10.72 kg
Package Level 3 Units	192 piece

External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> lec Contactors
E-Number (Finland)	3707136
E-Number (Sweden)	3210056

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF96

