



PRODUCT-DETAILS**T5 630 P FP 3p HR****T5 630 P FP 3p HR**

General Information

| | |
|-----------------------|---|
| Extended Product Type | T5 630 P FP 3p HR |
| Product ID | 1SDA054764R1 |
| EAN | 8015644558932 |
| Catalog Description | T5 630 P FP 3p HR |
| Long Description | FIXED PART PLUG-IN FOR C.BREAKER TMAX THREE-POLE WITH REAR TERMINALS HORIZONTAL T5 630 |

ABB EcoSolutions

| | |
|---|-----------------------|
| Environmental Product Declaration - EPD | No declaration needed |
|---|-----------------------|

Material Compliance

| | |
|-------------------|--|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

Environmental

| | |
|---------------------------|-----------------|
| Environmental Information | 9AKK108467A6707 |
|---------------------------|-----------------|

Ordering

| | |
|--------------------------|---------------|
| Order Code US and Canada | KT56PFHR |
| E-Number (Finland) | 3655573 |
| EAN | 8015644558932 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width | 171 mm |
| Product Net Height | 273 mm |
| Product Net Depth / Length | 50 mm |
| Product Net Weight | 1.5 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 228 mm |
| Package Level 1 Height | 228 mm |
| Package Level 1 Depth / Length | 286 mm |
| Package Level 1 Gross Weight | 1.7 kg |
| Package Level 1 EAN | 8015644558932 |

Additional Information

| | |
|----------------------------|-------------------------------|
| Product Main Type | Accessories for Tmax T |
| Product Name | Accessory |
| Product Type | Fixed Part |
| Suitable For | T5 |
| Suitable for Product Class | Moulded Case Circuit Breakers |
| Version | P |

Technical

| | |
|-----------------|------------|
| Device | Fixed Part |
| Number of Poles | 3P |

| | |
|---|--|
| Rated Operational Voltage | 690 V AC 750 V DC |
| Rated Uninterrupted Current (I _u) | 630 A |
| Standards | IEC |
| Sub-type | T5 |
| Terminal Connection Type | Plug-In Circuit-Breakers Rear flat Horizontal |
| Test Voltage at Industrial Frequency for 1 Minute | not applicable V |

Certificates and Declarations

| | |
|-----------------------------------|---|
| Data Sheet, Technical Information | 1SDC210004D0203 |
| Declaration of Conformity - CE | Refer to the EU Declaration of the relative Circuit Breaker |
| Instructions and Manuals | 1SDH000437R0001 |
| Instructions and Manuals (Part 2) | ITSCE-RH0100001 |

External Classifications and Standards

| | |
|----------------------------|--|
| ETIM 8 | EC002043 - Chassis part power circuit breaker |
| ETIM 9 | EC002043 - Chassis part power circuit breaker |
| Object Classification Code | Q |
| UNSPSC | 39121100 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370422 |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

