




---

 PRODUCT-DETAILS

# E2B1600PR121/P-LIIn=1600A3pWMP

## E2B 1600 PR121/P-LI In=1600A 3p W MP




---

**General Information**

Extended Product Type	E2B1600PR121/P-LIIn=1600A3pWMP
Product ID	1SDA055808R1
EAN	8015644571481
Catalog Description	E2B 1600 PR121/P-LI In=1600A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E2B 1600A THRE-POLE OVERCURRENT RELEASE PR121/P-LI R1600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

---

**Material Compliance**

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

---

**Environmental**

Environmental Information	9AKK10103A6076
---------------------------	----------------

---

**Ordering**


---

EAN	8015644571481
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

---



---

**Dimensions**


---

Product Net Width	324 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	49 kg

---



---

**Container Information**


---

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	59 kg
Package Level 1 EAN	8015644571481

---



---

**Additional Information**


---

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

---



---

**Technical**


---

Current Type	AC
Electrical Durability	Ue =< 440 V 12000 cycle Ue = 500 ... 690 V 10000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	215 W
Rated Current ( $I_n$ )	1600 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Current ( $I_e$ )	1600 A
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(220 V AC) 42 kA (230 V AC) 42 kA (380 V AC) 42 kA (400 V AC) 42 kA (415 V AC) 42 kA (440 V AC) 42 kA (500 V AC) 42 kA

	(660 V AC) 42 kA (690 V AC) 42 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 42 kA for 3 s 42 kA
Rated Ultimate Short- Circuit Breaking Capacity ( $I_{cu}$ )	(220 V AC) 42 kA (230 V AC) 42 kA (380 V AC) 42 kA (400 V AC) 42 kA (415 V AC) 42 kA (440 V AC) 42 kA (500 V AC) 42 kA (660 V AC) 42 kA (690 V AC) 42 kA
Rated Uninterrupted Current ( $I_u$ )	1600 A
Rated Voltage ( $U_r$ )	690 V
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	B
Standards	IEC
Sub-type	E2
Terminal Connection Type	Withdrawable Circuit-Breakers

## Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000460R0002

## External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

