




---

 PRODUCT-DETAILS

# E2N1250PR121/P-LSIIn=1250A4pFHR

## E2N 1250 PR121/P-LSI In=1250A 4p F HR




---

**General Information**

Extended Product Type	E2N1250PR121/P-LSIIn=1250A4pFHR
Product ID	1SDA055865R1
EAN	8015644572051
Catalog Description	E2N 1250 PR121/P-LSI In=1250A 4p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2N 1250A FOUR-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSI R1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

---

**Material Compliance**

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

## Environmental

Environmental Information	9AKK10103A6076
---------------------------	----------------

## Ordering

EAN	8015644572051
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

## Dimensions

Product Net Width	386 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	56 kg

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	68 kg
Package Level 1 EAN	8015644572051

## Additional Information

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F

## Technical

Current Type	AC
Electrical Durability	Ue = < 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	4P
Power Loss	70 W
Rated Current (I <sub>n</sub> )	1250 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	1000 V
Rated Operational	1250 A

Current (I <sub>e</sub> )	
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	(220 V AC) 65 kA (230 V AC) 65 kA (380 V AC) 65 kA (400 V AC) 65 kA (415 V AC) 65 kA (440 V AC) 65 kA (500 V AC) 55 kA (660 V AC) 55 kA (690 V AC) 55 kA
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 55 kA for 3 s 42 kA
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )	(220 V AC) 65 kA (230 V AC) 65 kA (380 V AC) 65 kA (400 V AC) 65 kA (415 V AC) 65 kA (440 V AC) 65 kA (500 V AC) 55 kA (660 V AC) 55 kA (690 V AC) 55 kA
Rated Uninterrupted Current (I <sub>u</sub> )	1250 A
Rated Voltage (U <sub>r</sub> )	690 V
Release	PR121/P-LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal

## Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000460R0002

## External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

