



PRODUCT-DETAILS

E3S3200PR122/P-LIIn=3200A3pWMP

E3S 3200 PR122/P-LI In=3200A 3p W MP



General Information	
Extended Product Type	E3S3200PR122/P-LIIn=3200A3pWMP
Product ID	1SDA056323R1
EAN	8015644576639
Catalog Description	E3S 3200 PR122/P-LI In=3200A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3S 3200A THRE-POLE OVERCURRENT RELEASE PR122/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	Document availability on demand
SCIP	c7acfc44-4a72-4273-85b6-eb1379897445 Italy
Simplified SCIP	3e1ab3e3-d946-4062-a017-60f64a19e1f3 Bulgaria 8c9a6e51-0d08-4384-8d5b-e6decfa22796 Poland

78968721-9101-4b37-b12c-b76a21ebd3f6	France
364e2ec5-c4fc-4036-a205-141e3d6a42e4	France
7c44f41d-4e6e-4a1d-adcf-283dc7a6d29a	Sweden
d949a6bc-c916-443d-bbf6-dfd0306bd6e2	Germany
41983400-8152-47e7-ba3a-650f2a0b4fb5	Estonia
8f25e543-9c54-4cc8-9f67-92f06327fa10	Germany
1d754a2c-cfdf-401d-94fc-e719f42593f6	Greece
e2a2b2a6-729e-4eba-86e6-e86a6f6791e0	Hungary
ad0d0571-12b7-414c-b9ff-6a6ec95d568a	Belgium
96749aa6-0fa0-4f49-add5-2e337d895163	Hungary
1d87acfa-23f4-4009-ae03-b64d70a56dcd	Sweden
ceb32e21-54dd-40f1-95bc-57d2ee1e47c9	Spain
8e6c25f0-e5e1-4d02-9555-319d1ee7df4c	Portugal
28c06403-68c1-4d42-8c7c-4758a091ea11	Denmark
a8dfcf46-3db4-4d17-8edd-8c8d51f8b3a7	Poland
c1e0a9a2-aff0-4855-8372-9bfceb16b02f	Finland
1f7fb2f4-5ce1-434a-a9ae-2c29fc95d2d9	Germany
b34ae4b3-6320-4257-b9e9-8f99659f4849	Germany
e51a479f-b19c-4c76-8bbc-4ba8ead55e45	Czech Republic
7363fbd-bf695-4fa7-a09f-a8aa66b268a0	Poland
daf76020-f1be-43ad-af12-5ee410108102	Germany
a6d6aaa2-6a04-417a-9287-7bf8e003deb6	Croatia
d5a42375-9e26-4167-8c8b-e94d93568281	Belgium
9fbc0efc-fc8d-4d18-a8b9-318ca9ff5305	Netherlands
98ebc7f9-8a5a-4226-ad37-cb522f55faa5	Norway

Environmental	
Environmental Information	9AKK10103A6076

Ordering	
EAN	8015644576639
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	77 kg
Package Level 1 EAN	8015644576639

Additional Information	
------------------------	--

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

Technical

Current Type	AC
Electrical Durability	Ue ≤ 440 V 6000 cycle Ue = 500 ... 690 V 5000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	570 W
Rated Current (I _N)	3200 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current (I _e)	3200 A
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 75 kA (230 V AC) 75 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 75 kA (500 V AC) 75 kA (660 V AC) 75 kA (690 V AC) 75 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 75 kA for 3 s 65 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 75 kA (230 V AC) 75 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 75 kA (500 V AC) 75 kA (660 V AC) 75 kA (690 V AC) 75 kA
Rated Uninterrupted Current (I _u)	3200 A
Rated Voltage (U _r)	690 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers

Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0015
Instructions and Manuals	1SDH000460R0002 1SDH000460R0102

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

