



PRODUCT-DETAILS

E2S800PR121/P-LIIn=800A4pFHR
E2S 800 PR121/P-LI In=800A 4p F HR



General Information	
Extended Product Type	E2S800PR121/P-LIIn=800A4pFHR
Product ID	1SDA058290R1
EAN	8015644605780
Catalog Description	E2S 800 PR121/P-LI In=800A 4p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E2S 800A FOUR-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Environmental	
Environmental Information	9AKK10103A6076

Ordering	
EAN	8015644605780
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions	
Product Net Width	386 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	56 kg

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	68 kg
Package Level 1 EAN	8015644605780

Additional Information	
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	E

Technical	
Current Type	AC
Electrical Durability	Ue =< 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	4P
Power Loss	29 W
Rated Current (I _n)	800 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current (I _e)	800 A
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA

	(660 V AC) 65 kA (690 V AC) 65 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 65 kA for 3 s 50 kA
Rated Ultimate Short- Circuit Breaking Capacity (I_{cu})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (660 V AC) 65 kA (690 V AC) 65 kA
Rated Uninterrupted Current (I_u)	800 A
Rated Voltage (U_r)	690 V
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal

Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0014
Instructions and Manuals	1SDH000460R0002

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

