

PRODUCT-DETAILS

E3S/MS12503pWMPnew E3S/MS 1250 3p W MP new



| General Information | |
|-----------------------|--|
| Extended Product Type | E3S/MS12503pWMPnew |
| Product ID | 1SDA058981R1 |
| EAN | 8015644613402 |
| Catalog Description | E3S/MS 1250 3p W MP new |
| Long Description | SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E3S/MS 1250A THREE-POLE NEW |

| Material Compliance | |
|---|--|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | Document availability on demand |

Environmental

Environmental 9AKK10103A6076 Information

| Ordering | |
|------------------------|---------------|
| EAN | 8015644613402 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

| Dimensions | |
|-------------------------------|----------|
| Product Net Width | 432 mm |
| Product Net Height | 461 mm |
| Product Net Depth / Length | 396.5 mm |
| Product Net Weight | 64 kg |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 515 mm |
| Package Level 1 Height | 600 mm |
| Package Level 1 Depth / Length | 615 mm |
| Package Level 1 Gross Weight | 77 kg |
| Package Level 1 EAN | 8015644609139 |

| Additional Information | |
|------------------------|---------------------|
| Product Main Type | SACE Emax |
| Product Name | Switch Disconnector |
| Product Type | Air Circuit Breaker |
| Version | W |

| Technical | |
|---|-----------------------------------|
| Current Type | AC |
| Electrical Durability | 12000 cycle 20 cycles per hour |
| Mechanical Durability | 20000 cycle 60 cycles per hour |
| Number of Poles | 3P |
| Power Loss | 90 W |
| Rated Current (In) | 1250 A |
| Rated Impulse Withstand Voltage (U _{imp}) | 12 kV |
| Rated Insulation Voltage (Ui) | 1000 V |
| Rated Operational Current (I _e) | 1250 A |
| Rated Operational | 690 V AC |
| Voltage | 250 V DC |

| Rated Short-time Withstand Current Low | for 1 s 75 kA for 3 s 65 kA |
|--|--------------------------------|
| Voltage (I _{cw}) | |
| Rated Uninterrupted Current (I _{II}) | 1250 A |
| Rated Voltage (U _r) | 690 V |
| Short-Circuit Performance Level | S |
| Standards | IEC |
| Sub-type | E3 |
| Terminal Connection Type | Withdrawable Circuit-Breakers |

| Certificates and Declarations | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200006D0209 |
| Declaration of Conformity - CE | 1SDL000165R0015 |
| Instructions and Manuals | 1SDH000460R0002 |

| External Classifications and Standards | |
|--|--|
| Object Classification Code | Q |
| UNSPSC | 39120000 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems \rightarrow Circuit Breakers \rightarrow Air Circuit Breakers \rightarrow Emax

