



 PRODUCT-DETAILS

E2N/MS10004pWMPnew

E2N/MS 1000 4p W MP new



General Information

| | |
|-----------------------|---|
| Extended Product Type | E2N/MS10004pWMPnew |
| Product ID | 1SDA059300R1 |
| EAN | 8015644616618 |
| Catalog Description | E2N/MS 1000 4p W MP new |
| Long Description | SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E2N/MS 1000A FOUR-POLE NEW |

Material Compliance

| | |
|---|--|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | Document availability on demand |

Environmental

Environmental
Information

9AKK10103A6076

Ordering

| | |
|------------------------|---------------|
| EAN | 8015644616618 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 414 mm |
| Product Net Height | 461 mm |
| Product Net Depth / Length | 396.5 mm |
| Product Net Weight | 61 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 515 mm |
| Package Level 1 Height | 600 mm |
| Package Level 1 Depth / Length | 615 mm |
| Package Level 1 Gross Weight | 73 kg |
| Package Level 1 EAN | 8015644609139 |

Additional Information

| | |
|-------------------|---------------------|
| Product Main Type | SACE Emax |
| Product Name | Switch Disconnecter |
| Product Type | Air Circuit Breaker |
| Version | W |

Technical

| | |
|---|-----------------------------------|
| Current Type | AC |
| Electrical Durability | 15000 cycle 30 cycles per hour |
| Mechanical Durability | 25000 cycle 60 cycles per hour |
| Number of Poles | 4P |
| Power Loss | 83.2 W |
| Rated Current (I_n) | 1000 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Current (I_e) | 1000 A |
| Rated Operational Voltage | 690 V AC 250 V DC |

| | |
|---|--------------------------------|
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 55 kA for 3 s 42 kA |
| Rated Uninterrupted Current (I_u) | 1000 A |
| Rated Voltage (U_r) | 690 V |
| Release Type | EL |
| Short-Circuit Performance Level | N |
| Standards | IEC |
| Sub-type | E2 |
| Terminal Connection Type | Withdrawable Circuit-Breakers |

Certificates and Declarations

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200006D0209 |
| Declaration of Conformity - CE | 1SDL000165R0014 |
| Instructions and Manuals | 1SDH000460R0002 |

External Classifications and Standards

| | |
|----------------------------|--|
| Object Classification Code | Q |
| UNSPSC | 39120000 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

