



PRODUCT-DETAILS

E3S1000PR122/P-LIIn=1000A3pWMP
E3S 1000 PR122/P-LI In=1000A 3p W MP



General Information	
Extended Product Type	E3S1000PR122/P-LIIn=1000A3pWMP
Product ID	1SDA059398R1
EAN	8015644617592
Catalog Description	E3S 1000 PR122/P-LI In=1000A 3p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3S 1000A THRE-POLE OVERCURRENT RELEASE PR122/P-LI R1000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Environmental

Environmental Information	9AKK10103A6076
---------------------------	----------------

Ordering

EAN	8015644617592
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	432 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	64 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	77 kg
Package Level 1 EAN	8015644609139

Additional Information

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

Technical

Current Type	AC
Electrical Durability	Ue = < 440 V 12000 cycle Ue = 500 ... 690 V 12000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	57.6 W
Rated Current (I _n)	1000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational	1000 A

Current (I_e)	
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 75 kA (230 V AC) 75 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 75 kA (500 V AC) 75 kA (660 V AC) 75 kA (690 V AC) 75 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 75 kA for 3 s 65 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 75 kA (230 V AC) 75 kA (380 V AC) 75 kA (400 V AC) 75 kA (415 V AC) 75 kA (440 V AC) 75 kA (500 V AC) 75 kA (660 V AC) 75 kA (690 V AC) 75 kA
Rated Uninterrupted Current (I_u)	1000 A
Rated Voltage (U_r)	690 V
Release	PR122/P-LI
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers

Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0015
Instructions and Manuals	1SDH000460R0002 1SDH000460R0102

External Classifications and Standards

Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

