



PRODUCT-DETAILS

T6N 800 TMA 800-8000 3p F F

T6N 800 TMA 800-8000 3p F F



General Information	
Extended Product Type	T6N 800 TMA 800-8000 3p F F
Product ID	1SDA060214R1
EAN	8015644626747
Catalog Description	T6N 800 TMA 800-8000 3p F F
Long Description	C.BREAKER TMAX T6N 800 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 800 I3=4000...8000 A

ABB EcoSolutions	
Environmental Product Declaration - EPD	No declaration needed

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK10103A1058 9AKK108467A6707
------------------------------	-----------------------------------

Ordering

EAN	8015644626747
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	9.082 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	305 mm
Package Level 1 Height	285 mm
Package Level 1 Depth / Length	370 mm
Package Level 1 Gross Weight	11 kg
Package Level 1 EAN	8015644626747

Additional Information

Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable For	T6
Suitable for Product Class	Moulded Case Circuit Breakers
Version	F

Technical

Electrical Durability	5000 cycle 60 cycles per hour
Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	3P

Power Loss	at Rated Operating Conditions per Pole 31 W	
Rated Current (I_n)	800 A	
Rated Impulse Withstand Voltage (U_{imp})	8 kV	
Rated Insulation Voltage (U_i)	1000 V	
Rated Operational Voltage	690 V AC 750 V DC	
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 15 kA	
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 10 kA	
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 36 kA (500 V DC) 2 Poles in Series 25 kA (750 V DC) 3 Poles in Series 16 kA	
Rated Uninterrupted Current (I_u)	800 A	
Release	TMA	
Release Type	TM	
Short-Circuit Performance Level	N	
Standards	IEC	
Sub-type	T6	
Terminal Connection Type	Fixed Circuit-Breakers Front	
Test Voltage Max (U_{test})	3500 V	

Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0201
Declaration of Conformity - CE	9AKK106713A5538
GL Certificate	1SDL000163R0057
Instructions and Manuals	1SDH000511R0001

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q

UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

