



PRODUCT-DETAILS

# E2.2N 2500 Ekip G Touch LSIG 3p F HR

## E2.2N 2500 Ekip G Touch LSIG 3p F HR



| General Information   |                                                                                                                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E2.2N 2500 Ekip G Touch LSIG 3p F HR                                                                                                                                                                          |
| Product ID            | 1SDA071067R1                                                                                                                                                                                                  |
| EAN                   | 8015644749170                                                                                                                                                                                                 |
| Catalog Description   | E2.2N 2500 Ekip G Touch LSIG 3p F HR                                                                                                                                                                          |
| Long Description      | C.BREAKER SACE EMAX2 E2.2N 2500 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC Ekip/G/TOUCH-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

| ABB EcoSolutions                                |                                                               |
|-------------------------------------------------|---------------------------------------------------------------|
| ABB EcoSolutions                                | Yes                                                           |
| ABB Site Meeting Group Waste To Landfill Target | UL 2799 Zero Waste To Landfill Validation available           |
| End Of Life Disassembling Instructions          | 9AKK108468A2361                                               |
| Environmental Product Declaration - EPD         | 9AKK108468A1902<br>9AKK108468A1909                            |
| Recyclability Rate of the                       | Design for Closing Resource Loops - Standard EN45555 - 79.1 % |

Product acc. to EN45555

**Material Compliance**

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| REACH Declaration                           | 9AKK108466A1425                                                        |
| RoHS Information                            | 9AKK108466A1424                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326                                                        |
| SCIP                                        | 5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy                             |

**Environmental**

|                           |                 |
|---------------------------|-----------------|
| Environmental Information | 9AKK108467A6707 |
|---------------------------|-----------------|

**Ordering**

|                          |                      |
|--------------------------|----------------------|
| Order Code US and Canada | Z2NUELBN200A000000XX |
| EAN                      | 8015644749170        |
| Minimum Order Quantity   | 1 piece              |
| Customs Tariff Number    | 85362090             |

**Dimensions**

|                            |        |
|----------------------------|--------|
| Product Net Width          | 276 mm |
| Product Net Height         | 371 mm |
| Product Net Depth / Length | 270 mm |
| Product Net Weight         | 41 kg  |

**Container Information**

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 515 mm        |
| Package Level 1 Height         | 610 mm        |
| Package Level 1 Depth / Length | 515 mm        |
| Package Level 1 Gross Weight   | 46 kg         |
| Package Level 1 EAN            | 8015644749170 |

**Additional Information**

|                   |                     |
|-------------------|---------------------|
| Product Main Type | SACE Emax 2         |
| Product Name      | Air Circuit Breaker |
| Product Type      | Air Circuit Breaker |
| Version           | F                   |

## Technical

|                                                                                                  |                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Current Type                                                                                     | AC                                                                                                                                                                               |
| Electrical Durability                                                                            | Ue ≤ 440 V 8000 cycle<br>Ue = 500 ... 690 V 7000 cycle<br>30 cycles per hour                                                                                                     |
| Mechanical Durability                                                                            | 20000 cycle<br>60 cycles per hour                                                                                                                                                |
| Number of Poles                                                                                  | 3P                                                                                                                                                                               |
| Power Loss                                                                                       | 267 W                                                                                                                                                                            |
| Rated Current (I <sub>n</sub> )                                                                  | 2500 A                                                                                                                                                                           |
| Rated Impulse<br>Withstand Voltage (U <sub>imp</sub> )                                           | acc. to IEC 60947-2 12 kV                                                                                                                                                        |
| Rated Insulation Voltage<br>(U <sub>i</sub> )                                                    | AC 1000 V                                                                                                                                                                        |
| Rated Operational<br>Voltage                                                                     | 690 V AC                                                                                                                                                                         |
| Rated Service Short-<br>Circuit Breaking<br>Capacity (I <sub>cs</sub> )                          | (220 V AC) 66 kA<br>(230 V AC) 66 kA<br>(380 V AC) 66 kA<br>(400 V AC) 66 kA<br>(415 V AC) 66 kA<br>(440 V AC) 66 kA<br>(500 V AC) 66 kA<br>(660 V AC) 66 kA<br>(690 V AC) 66 kA |
| Rated Service Short-<br>Circuit Breaking<br>Capacity, in % of I <sub>cu</sub> (I <sub>cs</sub> ) | 100 %                                                                                                                                                                            |
| Rated Short-time<br>Withstand Current Low<br>Voltage (I <sub>cw</sub> )                          | for 1 s 66 kA<br>for 3 s 50 kA                                                                                                                                                   |
| Rated Ultimate Short-<br>Circuit Breaking<br>Capacity (I <sub>cu</sub> )                         | (400 V AC) 66 kA<br>(415 V AC) 66 kA<br>(440 V AC) 66 kA<br>(500 V AC) 66 kA<br>(525 V AC) 66 kA<br>(690 V AC) 66 kA                                                             |
| Rated Uninterrupted<br>Current (I <sub>u</sub> )                                                 | 2500 A                                                                                                                                                                           |
| Rated Voltage (U <sub>r</sub> )                                                                  | 690 V                                                                                                                                                                            |
| Release                                                                                          | Ekip G Touch LSIG                                                                                                                                                                |
| Release Type                                                                                     | EL                                                                                                                                                                               |
| Short-Circuit<br>Performance Level                                                               | N                                                                                                                                                                                |
| Standards                                                                                        | IEC                                                                                                                                                                              |
| Sub-type                                                                                         | E2.2                                                                                                                                                                             |
| Suitable for IT Networks                                                                         | Yes, 690V                                                                                                                                                                        |
| Terminal Connection<br>Type                                                                      | Rear flat Horizontal                                                                                                                                                             |

## Certificates and Declarations

|                                      |                 |
|--------------------------------------|-----------------|
| Data Sheet, Technical<br>Information | 1SDC200023D0209 |
| Declaration of<br>Conformity - CE    | 9AKK106713A5902 |
| Instructions and<br>Manuals          | 1SDH001000R0002 |

External Classifications and Standards

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| ETIM 8                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers                                                 |
| Object Classification Code         | Q                                                                            |
| UNSPSC                             | 39121615                                                                     |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                             | V11.1 : 27370409                                                             |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

