



PRODUCT-DETAILS

E2.2N 1000 Ekip Touch LSI 4p F HR

E2.2N 1000 Ekip Touch LSI 4p F HR



	E2.2N 1000 Ekip Touch LSI 4p F HR
	1SDA071555R1
(EAN)	8015644754051
	E2.2N 1000 Ekip Touch LSI 4p F HR
	C.BREAKER SACE EMAX2 E2.2N 1000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 1000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	
ABB	UL 2799 Zero Waste To Landfill Validation available
	9AKK108468A2361
- EPD	9AKK108468A1902 9AKK108468A1909
EN45555	Design for Closing Resource Loops - Standard EN45555 - 79.1 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS	9AKK108466A1424
RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy

	9AKK108467A6707

USCON	ZBNQEGBE000A000000XX
(EAN)	8015644754051
	1 piece
	85362090

	366 mm
	371 mm
	270 mm
	53 kg

1	box 1 piece
1	515 mm
1	610 mm
1	615 mm
1	58 kg
1 EAN	8015644754051

	SACE Emax 2
	Air Circuit Breaker
	Air Circuit Breaker
	F
CAD Dimensional Drawing	1SDH001252R0123

	AC
	Ue ≤ 440 V 15000 cycle
	Ue = 500 ... 690 V 15000 cycle
	30 cycles per hour
	25000 cycle
	60 cycles per hour

额定电流 (I _N)	100 %
额定电压 (U _N)	4P
额定功率 (S _N)	53 W
额定短路电流 (I _{sc})	1000 A
额定短路容量 (S _{sc})	acc. to IEC 60947-2 12 kV
额定电压 (U _i)	AC 1000 V
额定电压 (U _e)	690 V AC
额定短路电流 (I _{cs})	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
额定短路容量 (S _{cs})	100 %
额定短路容量 (I _{cu})	for 1 s 66 kA for 3 s 50 kA
额定短路容量 (I _{cu})	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
额定电压 (U _e)	1000 A
额定电压 (U _r)	690 V
额定电压	Main Circuit M12
额定电压	Ekip Touch LSI
额定电压	EL
额定电压	N
额定电压	IEC
额定电压	E2.2
Suitable for IT Networks	Yes, 690V
额定电压	Rear flat Horizontal
额定电压	Bolt
额定电压	70 N·m

ATEX	No certification needed
CSA	No certification needed
CSA	No certification needed
CSA	1SXF200023C2001
UL - CE	9AKK106713A5902
UL	No certification needed
VDE	No certification needed
SDH001000R0100	1SDH001000R0100
SDM000091R0001	1SDM000091R0001
SDH001000R0006	1SDH001000R0006
SDH001316R1002	1SDH001316R1002

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA (IGCC)	4926 >> Air circuit breakers
Q	Q

UNSPSC	39121615
WEEE 	5. Small Equipment (No External Dimension More Than 50 cm)
	V11.1 : 27370409



 →  →  → Emax 2

