



 PRODUCT-DETAILS

E1.2N 630 Ekip Hi-Touch LSI 3p WMP

E1.2N 630 Ekip Hi-Touch LSI 3p WMP



General Information

Extended Product Type	E1.2N 630 Ekip Hi-Touch LSI 3p WMP
Product ID	1SDA072078R1
EAN	8015644759285
Catalog Description	E1.2N 630 Ekip Hi-Touch LSI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2N 630 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSI R 630 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2360
Environmental Product Declaration - EPD	9AKK108468A1900 9AKK108468A3028
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 76.4 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	Z1NNEAJ200A000000XX
EAN	8015644759285
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	278 mm
Product Net Height	363.5 mm
Product Net Depth / Length	271 mm
Product Net Weight	18 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	20 kg
Package Level 1 EAN	8015644759285

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W
CAD Dimensional Drawing	1SDH001252R0024

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour

Number of Poles	3P
Power Loss	62 W
Rated Current (I_n)	630 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA
Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA for 3 s 30 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I_U)	630 A
Rated Voltage (U_r)	690 V
Release	Ekip Hi-Touch LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E1.2
Suitable for IT Networks	Yes, 690V

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0109 1SDC200023D0209 1SDC200023D0709 1SDC200023D0309 1SDC200023D0909 1SXF200023C2001
Declaration of Conformity - CE	9AKK106713A5546
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH000999R0103
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH000999R0003 1SDH000999R0002 1SDH000999R0005 1SDH000999R0004 1SDH000999R0001 1SDH000999R0006
Instructions and Manuals (Part 2)	1SDH001316R1003 1SDH001316R1002

1SDH001316R1005
 1SDH001316R1004
 1SDH001316R1001

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

