



 PRODUCT-DETAILS

E1.2C 1000 Ekip Touch LSI 3p WMP

E1.2C 1000 Ekip Touch LSI 3p WMP



General Information

Extended Product Type	E1.2C 1000 Ekip Touch LSI 3p WMP
Product ID	1SDA072145R1
EAN	8015644759957
Catalog Description	E1.2C 1000 Ekip Touch LSI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2C 1000 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 1000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2360
Environmental Product Declaration - EPD	9AKK108468A1900 9AKK108468A3028
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 76.4 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	51117947-33e6-4b42-9ee1-5d26530f78b0 Italy
Simplified SCIP	7517f80a-8bd9-4f67-8475-d766923f741e Germany 9da6a923-f13e-415b-ab8f-5f8baa781d8f Netherlands 672eecff-284f-44f6-a465-e0ac55774002 Greece 2966004e-12e9-4521-a80f-0cf520606663 Estonia 739d5934-7859-4b8e-adb3-8ad0733e44d0 Portugal 90ac74b6-a46c-45d0-ac83-1541cfafaa8a Bulgaria 1c4a130f-8ed3-48b6-9730-e4a44fd02c5a Sweden 0361a97f-36bb-4d5a-a0d6-d8e2c07b226d Poland 48a1abfb-5fa7-4a7b-94d3-25c22ae6ce1a Hungary 2b9f9a7e-c1ed-4b7f-a10d-db5925be0fe8 Poland a8d2337d-db75-47c8-b747-0bbbce242a40 Czech Republic c944054f-11f4-4a13-adf3-ab95aeb4b8ac Germany c3239deb-3d0a-4584-b282-2e9fc956f955 Germany 6462d5c3-1ee9-440d-9ddd-984ab99bec8b Germany 4c92115d-6f1c-4f0f-a99b-0d8a20268eea Poland f7b845ef-d19d-4a2b-b0b4-e5005ee9b411 Norway ed0cafd8-3f71-4309-bcc6-8b29974e8ed4 Denmark de595a53-3498-4a03-91fa-b017703dbdfd Germany e0668c00-bc10-49f7-9ca7-c341f0bf2dbd France 19eedc17-ff81-419f-b870-4bb0cfbc2acf Croatia 0344fe76-8705-491c-b99b-47d816ea2553 Finland 32597214-06d5-42f2-8d6f-b8d2ade07584 Belgium 24f06968-4206-475b-991d-a506d7ca4cb2 Sweden 274b5ea6-57f7-4d23-99f2-55d3583a63c4 Belgium c35cbb4a-419b-4861-a210-2358a89b42d5 Spain d9367f52-af05-412d-af45-af0ace1ab756 France 1c7123c5-7f88-4d78-accce-e1e1b0eeae89 Hungary

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	Z1CQEGAE000A000000XX
EAN	8015644759957
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	278 mm
Product Net Height	363.5 mm
Product Net Depth / Length	271 mm
Product Net Weight	18 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm

Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	20 kg
Package Level 1 EAN	8015644759957

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W
CAD Dimensional Drawing	1SDH001252R0024

Technical

Current Type	AC
Electrical Durability	U _e =< 440 V 8000 cycle U _e = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	156 W
Rated Current (I _n)	1000 A
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 50 kA (230 V AC) 50 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 42 kA (660 V AC) 42 kA (690 V AC) 42 kA
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 42 kA for 3 s 24 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 42 kA (525 V AC) 42 kA (690 V AC) 42 kA
Rated Uninterrupted Current (I _u)	1000 A
Rated Voltage (U _r)	690 V
Release	Ekip Touch LSI
Release Type	EL
Short-Circuit Performance Level	C
Standards	IEC
Sub-type	E1.2
Suitable for IT Networks	Yes, 690V

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH000999R0103
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH000999R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

