




---

 PRODUCT-DETAILS

# E2.2N 1250 Ekip G Hi-Touch LSIG 3p WMP

## E2.2N 1250 Ekip G Hi-Touch LSIG 3p WMP




---

**General Information**

Extended Product Type	E2.2N 1250 Ekip G Hi-Touch LSIG 3p WMP
Product ID	1SDA072310R1
EAN	8015644761608
Catalog Description	E2.2N 1250 Ekip G Hi-Touch LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2N 1250 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/G/HI-TOUCH-LSIG R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

---

**ABB EcoSolutions**

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2361
Environmental Product Declaration - EPD	9AKK108468A1902 9AKK108468A1909
Recyclability Rate of the	Design for Closing Resource Loops - Standard EN45555 - 79.1 %

Product acc. to EN45555

**Material Compliance**

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy

**Environmental**

Environmental Information	9AKK108467A6707
---------------------------	-----------------

**Ordering**

Order Code US and Canada	Z2NREHAQ200A000000XX
EAN	8015644761608
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

**Dimensions**

Product Net Width	317 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	48 kg

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	53 kg
Package Level 1 EAN	8015644761608

**Additional Information**

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

## Technical

Current Type	AC
Electrical Durability	U <sub>e</sub> = < 440 V 15000 cycle U <sub>e</sub> = 500 ... 690 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	176 W
Rated Current (I <sub>n</sub> )	1250 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U <sub>i</sub> )	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cu</sub> (I <sub>cs</sub> )	100 %
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I <sub>u</sub> )	1250 A
Rated Voltage (U <sub>r</sub> )	690 V
Release	Ekip G Hi-Touch LSiG
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E2.2
Suitable for IT Networks	Yes, 690V

## Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

---

**External Classifications and Standards**

---

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

---

**Categories**

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

