



 PRODUCT-DETAILS

E1.2B/MS 1250 3p F F

E1.2B/MS 1250 3p F F



General Information

Extended Product Type	E1.2B/MS 1250 3p F F
Product ID	1SDA073398R1
EAN	8015644772482
Catalog Description	E1.2B/MS 1250 3p F F
Long Description	C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E1.2B/MS 1250 FIXED THREE-POLE WITH FRONT TERMINALS

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2360
Environmental Product Declaration - EPD	9AKK108468A1900 9AKK108468A3028
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 76.4 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	Z1BR00B00000000000XX
EAN	8015644772482
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	296 mm
Product Net Depth / Length	183 mm
Product Net Weight	14 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	16 kg
Package Level 1 EAN	8015644772482

Additional Information

Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Version	F
CAD Dimensional Drawing	1SDH001252R0001

Technical

Current Type	AC
Electrical Durability	8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle

	60 cycles per hour
Number of Poles	3P
Power Loss	122 W
Rated Current (I_n)	1250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 42 kA for 3 s 24 kA
Rated Uninterrupted Current (I_U)	1250 A
Rated Voltage (U_r)	690 V
Recommended Screw Driver	Main Circuit M10
Short-Circuit Performance Level	B
Standards	IEC
Sub-type	E1.2
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	45 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH000999R0101
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH000999R0002

External Classifications and Standards

ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
Object Classification Code	Q
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

