




---

 PRODUCT-DETAILS

# E2.2H/MS 1250 3p F HR

# E2.2H/MS 1250 3p F HR




---

**General Information**

Extended Product Type	E2.2H/MS 1250 3p F HR
Product ID	1SDA073407R1
EAN	8015644772574
Catalog Description	E2.2H/MS 1250 3p F HR
Long Description	C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E2.2H/MS 1250 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL

---

**ABB EcoSolutions**

ABB EcoSolutions	Yes
ABB Site Meeting Group	UL 2799 Zero Waste To Landfill Validation available
Waste To Landfill Target	
End Of Life Disassembling Instructions	9AKK108468A2361
Environmental Product Declaration - EPD	9AKK108468A1902 9AKK108468A1909
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 79.1 %

---

## Material Compliance

---

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

---



---

## Environmental

---

Environmental Information	9AKK108467A6707
---------------------------	-----------------

---



---

## Ordering

---

Order Code US and Canada	Z2HR00B00000000000XX
EAN	8015644772574
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

---



---

## Dimensions

---

Product Net Width	276 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	41 kg

---



---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	46 kg
Package Level 1 EAN	8015644772574

---



---

## Additional Information

---

Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Version	F
CAD Dimensional Drawing	1SDH001252R0083

---



---

## Technical

---

Current Type	AC
Electrical Durability	Ue =< 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle 30 cycles per hour

Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	83 W
Rated Current ( $I_n$ )	1250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 85 kA for 3 s 66 kA
Rated Uninterrupted Current ( $I_U$ )	1250 A
Rated Voltage ( $U_r$ )	690 V
Recommended Screw Driver	Main Circuit M12
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

## Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001000R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002

## External Classifications and Standards

ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnector
Object Classification Code	Q
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

