



English ▼



E2.2 W FP Iu=2000 4p HR HR

[Print to PDF](#)

[Buy now](#)

General Information

Extended Product Type:

E2.2 W FP Iu=2000 4p HR HR

Product ID:

1SDA073910R1

EAN:

8015644778439

Catalog Description:

E2.2 W FP Iu=2000 4p HR HR

Long Description:

FIXED PART WITHDRAWABLE FOR C.BREAKER SACE EMAX2 E2.2 2000 FOUR-POLE WITH REAR HORIZONTAL TERMINALS

[Add to Cart](#)

[Read More](#)

[Data Sheet](#)

[Downloads](#)

[Buy now](#)

[Categories](#)

[Related Links](#)

Go To Section:[ABB EcoSolutions](#)[Material Compliance](#)[Environmental](#)[Ordering](#)[Dimensions](#)[Container Information](#)[Additional Information](#)[Technical](#)[Certificates and Declarations](#)[External Classifications and Standards](#)**ABB EcoSolutions****Material Compliance****REACH Declaration:**[REACH Declaration ABB Sace circuit breakers](#)

RoHS Information:[RoHS Declaration ABB Sace circuit breakers](#)

RoHS Status:

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT):[CMRT - Conflict Minerals Reporting Template](#)

Toxic Substances Control Act - TSCA:[Toxic Substances Control Act \(TSCA\) declaration](#)

Environmental**Environmental Information:**[Breakers - Packaging disposal information](#)

Ordering**Order Code US and Canada:**

ZBC20A0XX

EAN:

8015644778439

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85389099

Dimensions**Product Net Width:**

407 mm

Product Net Height:

425 mm

Product Net Depth / Length:

383 mm

Product Net Weight:

44 kg

Container Information**Package Level 1 Units:**

box 1 piece

Package Level 1 Width:

570 mm

Package Level 1 Height:

610 mm

Package Level 1 Depth / Length:

615 mm

Package Level 1 Gross Weight:

49 kg

Package Level 1 EAN:

8015644778439

Additional Information**Product Main Type:**

SACE Emax 2

Product Name:

Fixed Part

Product Type:

Fixed Part

Version:

W FP

Technical**Current Type:**

AC

Electrical Durability:

2000 cycle

Mechanical Durability:

25000 cycle

60 cycles per hour

Neutral Pole Current ([%I_n]):

100 %

Number of Poles:

4P

Rated Current (I_n):

2000 A

Rated Impulse Withstand Voltage (U_{imp}):

acc. to IEC 60947-2 12 kV

Rated Insulation Voltage (U_i):

AC 1000 V

Rated Operational Voltage:

690 V AC

800 V AC

900 V AC

Rated Uninterrupted Current (I_u):

2000 A

Rated Voltage (U_r):

690 V

Recommended Screw Driver:

Main Circuit M12

Standards:

IEC

Sub-type:

E2.2

Terminal Connection Type:

Rear flat Horizontal

Terminal Type:

Bolt

Tightening Torque:

70 N·m

Certificates and Declarations**ATEX Certificate:**

No certification needed

CSA Certificate:

No certification needed

CSA Certificate (Intrinsic Safe):

No certification needed

Data Sheet, Technical Information:

[SACE Emax 2. New low voltage air circuit-breakers](#)

Declaration of Conformity - CE:

[EC Declaration of Conformity Emax E2.2](#)

UL Certificate:

No certification needed

VDE Certificate:

No certification needed

Instructions and Manuals:

[Fixed part of withdrawable circuit-breaker - E2.2-E4.2-E6.2](#)

External Classifications and Standards**ETIM 8:**

EC002043 - Chassis part power circuit breaker

ETIM 9:

EC002043 - Chassis part power circuit breaker

IDEA Granular Category Code (IGCC):

4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers

Object Classification Code:

Q

UNSPSC:

39121616

WEEE Category:

5. Small Equipment (No External Dimension More Than 50 cm)

eClass:

V11.1 : 27370422



PRODUCTS

[Offerings A-Z](#)

[Services](#)

[Where to buy](#)

INDUSTRY SOLUTIONS

[Channel partners](#)

[Buildings and infrastructure](#)

[Industrial automation](#)

[Marine](#)

[Oil & gas](#)

[Power generation](#)

INVESTORS

[Investor & shareholder resources](#)

[Quarterly results & annual reports](#)

[Corporate governance](#)

[Calendar, events and publications](#)

COMPANY

[Customer events](#)

[News & media](#)

[Who we are](#)

[Innovation](#)

[Careers](#)

[Sustainability](#)

[Our values](#)

[Supplying](#)



[Provider information](#)

[Privacy Notice](#)

[Cookie settings](#)

© 1995 - 2025