





AF265-30-11-12

Print to PDF

Buy now

General Information

Extended Product Type:

AF265-30-11-12

Product ID:

1SFL547002R1211

EAN:

7320500481165

Catalog Description:

AF265-30-11-12 Contactor

Long Description:

The AF265-30-11-12 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted auxiliary contacts and Main Circuit Bars, controlling motors up to 132 kW / 400 V AC (AC-3) or 200 hp / 480 V UL and switching power circuits up to 400 A (AC-1) or 350 A UL general use. Thank: to the AF technology, th... [Show more](#)

Add to Cart

Read More

Data Sheet

Downloads

Buy now

Categories

Related Links

Related Products

Go To Section:

- Ordering
- Popular Downloads
- Dimensions
- Technical
- Technical UL/CSA
- Environmental
- Material Compliance
- ABB EcoSolutions
- Certificates and Declarations
- Container Information
- External Classifications and Standards
- Accessories

Ordering

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85364900

Popular Downloads

Data Sheet, Technical Information:

[1SBC100214C0202 - Main catalog Motor protection and control Manual motor starters, contactors and overload relays \(PDF\) - Edition 2024](#)

Data Sheet, Technical Information (Part 2):

[Contactors and Overload relays guide](#)

Instructions and Manuals:

[Operating instruction, Contactor, AF\(S\)190 ... AF\(S\)370](#)

CAD Dimensional Drawing:

[Information - 2D and 3D files for CAD systems](#)

Dimension Diagram:

[Dimension Drawing, Contactor, AF265, AF305, AF370](#)

Dimensions

Product Net Width:

140 mm

Product Net Depth / Length:

180 mm

Product Net Height:

225 mm

Product Net Weight:

3.9 kg

Technical

Number of Main Contacts NO:

3

Number of Main Contacts NC:

0

Number of Auxiliary Contacts NO:

1

Number of Auxiliary Contacts NC:

1

Number of Poles:

3P

Rated Operational Voltage:

Main Circuit 1000 V

Rated Frequency (f):

Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I_{th}):acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 400 A**Rated Operational Current AC-1 (I_e):**

(1000 V) 40 °C 350 A

(1000 V) 55 °C 300 A

(1000 V) 60 °C 300 A

(1000 V) 70 °C 240 A

(690 V) 40 °C 400 A

(690 V) 55 °C 350 A

(690 V) 70 °C 290 A

Rated Operational Current AC-3 (I_e):

(415 V) 55 °C 265 A

(440 V) 55 °C 265 A

(500 V) 55 °C 250 A

(690 V) 55 °C 250 A

(1000 V) 55 °C 113 A

(380 / 400 V) 55 °C 265 A

(220 / 230 / 240 V) 55 °C 265 A

Rated Operational Current DC-1 (I_e):

(110 V) 2 Poles in Series, 40 °C 350 A

(220 V) 3 Poles in Series, 40 °C 350 A

Rated Operational Current DC-3 (I_e):

(110 V) 2 Poles in Series, 40 °C 350 A

(220 V) 3 Poles in Series, 40 °C 350 A

Rated Operational Current DC-5 (I_e):

(110 V) 2 Poles in Series, 40 °C 350 A

(220 V) 3 Poles in Series, 40 °C 350 A

Rated Operational Power AC-3 (P_e):

(415 V) 132 kW

(440 V) 160 kW

(500 V) 160 kW

(690 V) 200 kW

(1000 V) 160 kW

(380 / 400 V) 132 kW

(220 / 230 / 240 V) 75 kW

Rated Breaking Capacity AC-3:8 x I_e AC-3**Rated Making Capacity AC-3:**10 x I_e AC-3**Short-Circuit Protective Devices:**

gG Type Fuses 500 A

Rated Short-time Withstand Current Low Voltage (I_{cw}):

at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2120 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 400 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 865 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 2650 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1224 A

Maximum Breaking Capacity:

cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 3800 A
 cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 3300 A

Rated Insulation Voltage (U_i):

acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
 acc. to UL/CSA 1000 V

Rated Impulse Withstand Voltage (U_{imp}):

Main Circuit 8 kV

Maximum Electrical Switching Frequency:

(AC-1) 300 cycles per hour
 (AC-2 / AC-4) 150 cycles per hour
 (AC-3) 300 cycles per hour

Mechanical Durability:

5 million

Maximum Mechanical Switching Frequency:

300 cycles per hour

Coil Operating Limits:

(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)

Rated Control Circuit Voltage (U_c):

50 Hz 48 ... 130 V
 60 Hz 48 ... 130 V
 DC Operation 48 ... 130 V

Coil Consumption:

Holding at Max. Rated Control Circuit Voltage 50 Hz 17 V·A
 Holding at Max. Rated Control Circuit Voltage 60 Hz 17 V·A
 Holding at Max. Rated Control Circuit Voltage DC 2.5 W
 Pull-in at Max. Rated Control Circuit Voltage 50 Hz 180 V·A
 Pull-in at Max. Rated Control Circuit Voltage 60 Hz 180 V·A
 Pull-in at Max. Rated Control Circuit Voltage DC 150 W

Power Loss:

at Rated Operating Conditions per Pole 14 W

Operate Time:

Between Coil De-energization and NO Contact Opening 37 ... 47 ms
 Between Coil Energization and NO Contact Closing 25 ... 55 ms

Connecting Capacity Main Circuit:

Flexible 2 x 70 ... 185 mm²
 Rigid Al-Cable 1 x 185 ... 240 mm²
 Rigid Cu-Cable 2 x 70 ... 185 mm²

Connecting Capacity Auxiliary Circuit:

Flexible with Ferrule 2x 0.75 ... 2.5 mm²
 Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm²
 Flexible 1x0.75 ... 2.5 mm²
 Solid 2 x 1 ... 4 mm²
 Stranded 2 x 1 ... 4 mm²

Connecting Capacity:

Flexible 2 x 70 ... 185 mm²
 Rigid Al-Cable 1 x 185 ... 240 mm²
 Rigid Cu-Cable 2 x 70 ... 185 mm²

Degree of Protection:

acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00

Tightening Torque:

Cable Lug 28 N·m
Main Circuit 22 ... 43 N·m

Terminal Type:

Main Circuit: Bars

Product Name:

Block Contactor

Technical UL/CSA**NEMA Size:**

5

Continuous Current Rating NEMA:

270 A

Horsepower Rating NEMA:

(200 V AC) Three Phase 75 Hp
(230 V AC) Three Phase 100 Hp
(460 V AC) Three Phase 200 Hp
(575 V AC) Three Phase 200 Hp

Maximum Operating Voltage UL/CSA:

Main Circuit 1000 V

General Use Rating UL/CSA:

(1000 V AC) 350 A

Horsepower Rating UL/CSA:

(200 V AC) Three Phase 75 hp
(208 V AC) Three Phase 75 hp
(220 ... 240 V AC) Three Phase 100 hp
(440 ... 480 V AC) Three Phase 200 hp
(550 ... 600 V AC) Three Phase 250 hp

Full Load Amps Motor Use:

(440 ... 480 V AC) Three Phase 240 A
(550 ... 600 V AC) Three Phase 242 A

Environmental**Ambient Air Temperature:**

Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C
Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C
Close to Contactor for Storage -40 ... 70 °C

Maximum Operating Altitude Permissible:

Without Derating 3000 m

Material Compliance**Conflict Minerals Reporting Template (CMRT):**

[CMRT - Conflict Minerals Reporting Template](#)

REACH Declaration:

[REACH - Letter of Confirmation for block contactors, contactor relays, installation contactors, mini contactors, mini contactor relays, thermal overload relays, electronic overload relays and related accessories](#)

RoHS Information:

[RoHS II declaration for block contactors, installation contactors, mini contactors, mini contactor relays, thermal overload relays, electronic overload relays and related accessories](#)

RoHS Status:

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA:

[Toxic Substances Control Act \(TSCA\) declaration for Contactors](#)

WEEE B2C / B2B:

Business To Business

WEEE Category:

5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:

Yes

ABB Site Meeting Group Waste To Landfill Target:

Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility

End Of Life Disassembling Instructions:

[End-of-life instruction - AF\(S\)265\(B\)-**\(RT\) to AF\(S\)370\(B\)-**\(RT\)](#)

Environmental Product Declaration - EPD:

[Environmental Product Declaration, Contactors, AF\(S\)265-AF\(S\)370 \(SE\)](#)

[Environmental product declaration, AF265, AF305, AF370 \(CN\) Contactors](#)

Improved Energy Efficiency for Customers:

Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line

Recyclability Rate of the Product acc. to EN45555:

Design for Closing Resource Loops - Standard EN45555 - 76.3 %

Sustainable Material Content in Product (wt. %):

Recycled Metal - 33 %

Certificates and Declarations

A2L Certificate – UL:

[UL Certificate of Compliance A2L, Contactor, AF190 - AF370](#)

ABS Certificate:

[ABS Approval, Contactor, AF116 ... AF370 \(Sweden\)](#)

BV Certificate:

[BV Certificate, Contactor, AF116-30 ... AF370-30...AF116-40...AF370-40](#)

CB Certificate:

[SE-89316](#)

CCS Certificate:

[CCS Certificate, Contactor, AF116 to AF2850 \(Sweden\)](#)

CQC Certificate:

[CQC Certificate, AC Contactor, AF265-**-*, AF305-**-*, AF370-**-*, AF265B-**-*, AF305B-**-*, AF370B-**-*, Made in Sweden](#)

[CQC Certificate, Contactor, AF265, AF305, AF370, Made in China](#)

Declaration of Conformity - CCC:

[CCC Declaration of Conformity, AC Contactor, AF265-**-*, AF305-**-*, AF370-**-*, AF265B-**-*, AF305B-**-*, AF370B-**-*, Made in Sweden](#)

[CCC Declaration of Conformity, Contactor, AF265, AF305, AF370, Made in China](#)

Declaration of Conformity - CE:

[CE Declaration of Conformity - Contactor - AF116...AF370](#)

Declaration of Conformity - UKCA:

[UK Declaration of Conformity - Contactors >100A](#)

DNV Certificate:

[DNV-certificate, Contactors, AF116-30...AF370-30 and AF116-40...AF370-40](#)

EAC Certificate:

[9AKK107046A8618](#)

GL Certificate:

[GL_95073-14HH](#)

LR Certificate:

[Lloyds register Certificate, Contactor, AF116-30 ... AF370-30, AF116-40...AF370-40](#)

PRS Certificate:

[PRS Certificate - AF116...AF1650](#)

RINA Certificate:

[RINA Certificate, AF95, AF110, AF145, AF185, AF210, AF260, AF300, AF400, AF460, AF580, AF750, AF1250, AF1350, AF1650, AF2050, AF2650, AF116, AF140, AF146, AF190, AF205, AF265, AF305, AF370](#)

RMRS Certificate:

[9AKK107045A6978](#)

UL Certificate:

[cULus Certificate, Contactor, AF265, AF305, AF370, AX260, AX300, AX370, AFS265, AFS305, AFS370](#)

UL Listing Card:

[UL_E36588](#)

Container Information

Package Level 1 Units:

box 1 piece

Package Level 1 Width:

263 mm

Package Level 1 Depth / Length:

203 mm

Package Level 1 Height:

289 mm

Package Level 1 Gross Weight:

4.6 kg

Package Level 1 EAN:

7320500481165

External Classifications and Standards

Object Classification Code:

Q

ETIM 7:

EC000066 - Power contactor, AC switching

ETIM 8:

EC000066 - Power contactor, AC switching

ETIM 9:

EC000066 - Power contactor, AC switching

eClass:

V11.0 : 27371003

UNSPSC:

39121529

IDEA Granular Category Code (IGCC):

4758 >> Iec Contactors

E-Number (Finland):

3706471

E-Number (Norway):

4117648

E-Number (Sweden):

3210154

Accessories

2 Products

Identifier	Description	Type	Qty	Unit Of Measure	Actions
1SFN170801R1001	RU19/120 LVRT-Module	RU19/120	1	piece	
1SFN170801R1002	RU19/240 LVRT-Module	RU19/240	1	piece	



PRODUCTS

Offerings A-Z

Services

Where to buy

INDUSTRY SOLUTIONS

Channel partners

Buildings and infrastructure

Industrial automation

Marine

Oil & gas

Power generation

INVESTORS

Investor & shareholder resources

Quarterly results & annual reports

Corporate governance

Calendar, events and publications

COMPANY

Customer events

News & media

Who we are

Innovation

Careers

Sustainability

Our values

Supplying



Provider
information

Privacy Notice

Cookie settings

© 1995 - 2025