






AF305-30-11-13

Print to PDF

Buy now

General Information

Extended Product Type:

AF305-30-11-13

Product ID:

1SFL587002R1311

EAN:

7320500481776

Catalog Description:

AF305-30-11-13 Contactor

Long Description:

The AF305-30-11-13 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted auxiliary contacts and Main Circuit Bars, controlling motors up to 160 kW / 400 V AC (AC-3) or 250 hp / 480 V UL and switching power circuits up to 500 A (AC-1) or 400 A UL general use. Thanks to the AF technology, th... [Show more](#)

Add to Cart

Read More

Data Sheet

Downloads

Buy now

Categories

Related Links

Related Products

Go To Section:

- Ordering
- Popular Downloads
- Dimensions
- Technical
- Technical UL/CSA
- Environmental
- Material Compliance
- ABB EcoSolutions
- Certificates and Declarations
- Container Information
- External Classifications and Standards
- Accessories

Ordering

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85364900

Popular Downloads

Data Sheet, Technical Information:

[1SBC100214C0202 - Main catalog Motor protection and control Manual motor starters, contactors and overload relays \(PDF\) - Edition 2024](#)

Data Sheet, Technical Information (Part 2):

[Contactors and Overload relays guide](#)

Instructions and Manuals:

[Operating instruction, Contactor, AF\(\\$\)~~190~~ ... AF\(\\$\)~~370~~](#)

CAD Dimensional Drawing:

[Information - 2D and 3D files for CAD systems](#)

Dimension Diagram:

[Dimension Drawing, Contactor, AF265, AF305, AF370](#)

Dimensions

Product Net Width:

140 mm

Product Net Depth / Length:

180 mm

Product Net Height:

225 mm

Product Net Weight:

3.9 kg

Technical

Number of Main Contacts NO:

3
Number of Main Contacts NC:
0
Number of Auxiliary Contacts NO:
1
Number of Auxiliary Contacts NC:
1
Number of Poles:
3P
Rated Operational Voltage:
Main Circuit 1000 V
Rated Frequency (f):
Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):
acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 500 A
Rated Operational Current AC-1 (I_e):
(1000 V) 40 °C 375 A (1000 V) 55 °C 325 A (1000 V) 60 °C 325 A (1000 V) 70 °C 260 A (690 V) 40 °C 500 A (690 V) 55 °C 400 A (690 V) 70 °C 325 A
Rated Operational Current AC-3 (I_e):
(415 V) 55 °C 305 A (440 V) 55 °C 305 A (500 V) 55 °C 290 A (690 V) 55 °C 290 A (1000 V) 55 °C 131 A (380 / 400 V) 55 °C 305 A (220 / 230 / 240 V) 55 °C 305 A
Rated Operational Current DC-1 (I_e):
(110 V) 1-Pole, 40 °C 500 A (220 V) 2 Poles in Series, 40 °C 500 A (220 V) 3 Poles in Series, 40 °C 500 A
Rated Operational Current DC-3 (I_e):
(110 V) 2 Poles in Series, 40 °C 400 A (220 V) 3 Poles in Series, 40 °C 400 A
Rated Operational Current DC-5 (I_e):
(110 V) 2 Poles in Series, 40 °C 400 A (220 V) 3 Poles in Series, 40 °C 400 A
Rated Operational Power AC-3 (P_e):
(415 V) 160 kW (440 V) 160 kW (500 V) 200 kW (690 V) 250 kW (1000 V) 185 kW (380 / 400 V) 160 kW (220 / 230 / 240 V) 90 kW
Rated Breaking Capacity AC-3:
8 x I _e AC-3
Rated Making Capacity AC-3:
10 x I _e AC-3
Short-Circuit Protective Devices:
gG Type Fuses 500 A

Rated Short-time Withstand Current Low Voltage (I_{cw}):

at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2440 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 500 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 996 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 3050 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1409 A

Maximum Breaking Capacity:

cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 4600 A
 cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 3800 A

Rated Insulation Voltage (U_i):

acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
 acc. to UL/CSA 1000 V

Rated Impulse Withstand Voltage (U_{imp}):

Main Circuit 8 kV

Maximum Electrical Switching Frequency:

(AC-1) 300 cycles per hour
 (AC-2 / AC-4) 150 cycles per hour
 (AC-3) 300 cycles per hour

Mechanical Durability:

5 million

Maximum Mechanical Switching Frequency:

300 cycles per hour

Coil Operating Limits:

(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)

Rated Control Circuit Voltage (U_c):

50 Hz 100 ... 250 V
 60 Hz 100 ... 250 V
 DC Operation 100 ... 250 V

Coil Consumption:

Holding at Max. Rated Control Circuit Voltage 50 Hz 17.5 V·A
 Holding at Max. Rated Control Circuit Voltage 60 Hz 17.5 V·A
 Holding at Max. Rated Control Circuit Voltage DC 4.5 W
 Pull-in at Max. Rated Control Circuit Voltage 50 Hz 385 V·A
 Pull-in at Max. Rated Control Circuit Voltage 60 Hz 385 V·A
 Pull-in at Max. Rated Control Circuit Voltage DC 410 W

Power Loss:

at Rated Operating Conditions per Pole 19 W

Operate Time:

Between Coil De-energization and NO Contact Opening 37 ... 47 ms
 Between Coil Energization and NO Contact Closing 25 ... 55 ms

Connecting Capacity Main Circuit:

Flexible 1 x 16 ... 240 mm²
 Rigid Al-Cable 1 x 185 ... 240 mm²
 Rigid Cu-Cable 2 x 70 ... 185 mm²

Connecting Capacity Auxiliary Circuit:

Flexible with Ferrule 1x 0.75 ... 2.5 mm²
 Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm²
 Flexible 1x0.75 ... 2.5 mm²
 Solid 2 x 1 ... 4 mm²
 Stranded 1 x 1 ... 4 mm²

Connecting Capacity:

Flexible 2 x 70 ... 185 mm²
 Rigid Al-Cable 1 x 185 ... 240 mm²
 Rigid Cu-Cable 2 x 70 ... 185 mm²

Degree of Protection:

acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00

Tightening Torque:

Cable Lug 28 N·m
Main Circuit 22 ... 43 N·m

Terminal Type:

Main Circuit: Bars

Product Name:

Block Contactor

Technical UL/CSA**Maximum Operating Voltage UL/CSA:**

Main Circuit 1000 V

General Use Rating UL/CSA:

(1000 V AC) 400 A

Horsepower Rating UL/CSA:

(200 V AC) Three Phase 100 hp
(208 V AC) Three Phase 100 hp
(220 ... 240 V AC) Three Phase 125 hp
(440 ... 480 V AC) Three Phase 250 hp
(550 ... 600 V AC) Three Phase 300 hp

Full Load Amps Motor Use:

(440 ... 480 V AC) Three Phase 302 A
(550 ... 600 V AC) Three Phase 289 A

Environmental**Ambient Air Temperature:**

Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C
Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C
Close to Contactor for Storage -40 ... 70 °C

Maximum Operating Altitude Permissible:

Without Derating 3000 m

Material Compliance**Conflict Minerals Reporting Template (CMRT):**

[CMRT - Conflict Minerals Reporting Template](#)

REACH Declaration:

[REACH - Letter of Confirmation for block contactors, contactor relays, installation contactors, mini contactors, mini contactor relays, thermal overload relays, electronic overload relays and related accessories](#)

RoHS Information:

[RoHS II declaration for block contactors, installation contactors, mini contactors, mini contactor relays, thermal overload relays, electronic overload relays and related accessories](#)

RoHS Status:

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA:

[Toxic Substances Control Act \(TSCA\) declaration for Contactors](#)

WEEE B2C / B2B:

Business To Business

WEEE Category:

5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:

Yes

ABB Site Meeting Group Waste To Landfill Target:

Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility

End Of Life Disassembling Instructions:

End-of-life instruction - AF(S)265(B)-**(RT) to AF(S)370(B)-**(RT)

Environmental Product Declaration - EPD:

Environmental Product Declaration, Contactors, AF(S)265-AF(S)370 (SE)

Environmental product declaration, AF265, AF305, AF370 (CN) Contactors

Improved Energy Efficiency for Customers:

Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line

Recyclability Rate of the Product acc. to EN45555:

Design for Closing Resource Loops - Standard EN45555 - 76.3 %

Sustainable Material Content in Product (wt. %):

Recycled Metal - 33 %

Certificates and Declarations

A2L Certificate – UL:

UL Certificate of Compliance A2L, Contactor, AF190 - AF370

ABS Certificate:

ABS Approval, Contactor, AF116 ... AF370 (Sweden)

BV Certificate:

BV Certificate, Contactor, AF116-30 ... AF370-30...AF116-40...AF370-40

CB Certificate:

SE-89316

CCS Certificate:

CCS Certificate, Contactor, AF116 to AF2850 (Sweden)

CQC Certificate:

CQC Certificate, AC Contactor, AF265-**-*, AF305-**-*, AF370-**-*, AF265B-**-*, AF305B-**-*, AF370B-**-*, Made in Sweden

CQC Certificate, Contactor, AF265, AF305, AF370, Made in China

Declaration of Conformity - CCC:

CCC Declaration of Conformity, AC Contactor, AF265-**-*, AF305-**-*, AF370-**-*, AF265B-**-*, AF305B-**-*, AF370B-**-*, Made in Sweden

CCC Declaration of Conformity, Contactor, AF265, AF305, AF370, Made in China

Declaration of Conformity - CE:

CE Declaration of Conformity - Contactor - AF116...AF370

Declaration of Conformity - UKCA:

UK Declaration of Conformity - Contactors >100A

DNV Certificate:

DNV-certificate, Contactors, AF116-30...AF370-30 and AF116-40...AF370-40

EAC Certificate:

9AKK107046A8618

GL Certificate:

GL_95073-14HH

LR Certificate:

Lloyds register Certificate, Contactor, AF116-30 ... AF370-30, AF116-40...AF370-40

PRS Certificate:

PRS Certificate - AF116...AF1650

RINA Certificate:

[RINA Certificate](#), [AF95](#), [AF110](#), [AF145](#), [AF185](#), [AF210](#), [AF260](#), [AF300](#), [AF400](#), [AF460](#), [AF580](#), [AF750](#), [AF1250](#), [AF1350](#), [AF1650](#), [AF2050](#), [AF2650](#), [AF116](#), [AF140](#), [AF146](#), [AF190](#), [AF205](#), [AF265](#), [AF305](#), [AF370](#)

RMRS Certificate:

[9AKK107045A6978](#)

UL Certificate:

[cULus Certificate](#), [Contactor](#), [AF265](#), [AF305](#), [AF370](#), [AX260](#), [AX300](#), [AX370](#), [AFS265](#), [AFS305](#), [AFS370](#)

UL Listing Card:

[UL_E36588](#)

Container Information**Package Level 1 Units:**

box 1 piece

Package Level 1 Width:

263 mm

Package Level 1 Depth / Length:

203 mm

Package Level 1 Height:

289 mm

Package Level 1 Gross Weight:

4.6 kg

Package Level 1 EAN:

7320500481776

External Classifications and Standards**Object Classification Code:**

Q

ETIM 7:

EC000066 - Power contactor, AC switching

ETIM 8:

EC000066 - Power contactor, AC switching

ETIM 9:

EC000066 - Power contactor, AC switching

eClass:

V11.0 : 27371003

UNSPSC:

39121529

IDEA Granular Category Code (IGCC):

4758 >> Iec Contactors

E-Number (Finland):

3706486

E-Number (Norway):

4117650

E-Number (Sweden):

3210163

Accessories

2 Products

Identifier	Description	Type	Qty	Unit Of Measure	Actions
1SFN170801R1001	RU19/120 LVRT-Module	RU19/120	1	piece	
1SFN170801R1002	RU19/240 LVRT-Module	RU19/240	1	piece	



PRODUCTS

- Offerings A-Z
- Services
- Where to buy

INDUSTRY SOLUTIONS

- Channel partners
- Buildings and infrastructure
- Industrial automation
- Marine
- Oil & gas
- Power generation

INVESTORS

- Investor & shareholder resources
- Quarterly results & annual reports
- Corporate governance
- Calendar, events and publications

COMPANY

- Customer events
- News & media
- Who we are
- Innovation
- Careers
- Sustainability
- Our values
- Supplying



Provider
information

Privacy Notice

Cookie settings

© 1995 - 2025