




---

 PRODUCT-DETAILS

# DDA802 A-63/0.03

## Residual Current Device Block




---

**General Information**

Extended Product Type	DDA802 A-63/0.03
Product ID	2CSB802101R1630
EAN	8012542920007
Catalog Description	Residual Current Device Block
Long Description	The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is suitable for assembly with MCBs S800 series up to 63A.

---

**Technical**

Type of Residual Current	Type A
Suitable For	S800S S800N S800C S800B
Maximum Surge Current	0.25 kA
Leakage Current Type	A
Number of Poles	2P

Operating Characteristic	Instantaneous
Connecting Capacity	Rigid 6 ... 50 mm <sup>2</sup> Flexible 6 ... 70 mm <sup>2</sup>

## Electrical

Short-Circuit Current Rating (SCCR)	0.03 ... 0.03 A
Rated Voltage (U <sub>r</sub> )	230 V AC 240 V AC 400 V AC
Rated Operational Voltage	400/690 V
Rated Insulation Voltage (U <sub>i</sub> )	690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Rated Current (I <sub>n</sub> )	63 A
Rated Residual Current	30 mA
Rated Frequency (f)	50 ... 60 Hz
Power Loss	9 W

## Material Compliance

RoHS Information	9AKK106713A5616
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20110608
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	bfb66ab0-4ff3-4d5f-97bf-90721676f180 Italy
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

## Environmental

Ambient Temperature	-25...60 °C
Ambient Air Temperature	Operation -25...60 °C
Degree of Protection	IP2X
Environmental Information	document not needed

## Dimensions

Width in Number of Modular Spacings	4.5
Product Net Width	81 mm
Product Net Height	108.2 mm
Product Net Depth / Length	82.3 mm

Product Net Weight	300 g
--------------------	-------

---

## Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.4 kg
E-Number (Norway)	1627036

---

## Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5616
--------------------------------	-----------------

---

## Installation

Instructions and Manuals	2CSB427001D0003
--------------------------	-----------------

---

## Popular Downloads

Data Sheet, Technical Information	2CSC400002D0209
-----------------------------------	-----------------

---

## External Classifications and Standards

ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
eClass	V11.0 : 27142210
Object Classification Code	F
Standards	IEC EN 60947-2 Ann. B

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs Accessories

