



 PRODUCT-DETAILS

F202 AC-63/0.1

Residual Current Circuit Breaker - 2P - Type AC - 100 mA - 63 A



General Information

Extended Product Type	F202 AC-63/0.1
Product ID	2CSF202001R2630
EAN	8012542780502
Catalog Description	Residual Current Circuit Breaker - 2P - Type AC - 100 mA - 63 A
Long Description	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.

ABB EcoSolutions

ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108469A3794
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 82.05 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
Sustainable Material Content in Packaging (wt. %)	Recycled Paper - 00 % Recycled Paper - 04 % Recycled Cardboard - 29 % Recycled Cardboard - 61 % Recycled Cardboard - 03 %

Extended Product Lifetime	Product Durability
End Of Life Disassembling Instructions	9AKK108470A1748
Environmental Product Declaration - EPD	9AKK108469A9642

Technical

Type of Residual Current	Type AC
Test Voltage (U _t)	110-254 V
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Power Supply Connection	Arbitrary
Electrical Endurance	1000 cycle
Number of Poles	2P
Number of Modular Spacings per DIN Rail	2
Operating Characteristic	Instantaneous
Tightening Torque	2.8 N·m
Accessory Type	Auxiliary contact Auxiliary/Signal contact Shunt trip Undervoltage release Overvoltage release Motor Operating Device Bottom fitting auxiliary contact Autoreclosing Unit Home automatic resetting unit
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal Cage Terminal Failsafe Biconnect Fork Top/Bottom Failsafe Biconnect Fork Bottom
Options Provided	None
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ²
Rated Cross-Section	4 - Multi-Wired 0...25 mm ² 1 - Solid-Core 25...25 mm ²
Wire Stripping Length	12 mm
Terminal Type	Screw Terminals

Electrical

Rated Voltage (U _r)	230 V
Rated Operational Voltage	230 V
Rated Insulation Voltage (U _i)	500 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Input Voltage Type	AC
Rated Current (I _n)	63 A
Rated Residual Current	100 mA
Rated Conditional Short-Circuit Current (I _{nc})	10 kA
Frequency (f)	50/60 Hz
Rated Frequency (f)	50 ... 60 Hz
Power Loss	at Rated Operating Conditions per Pole 3.2 W Total 6.4 W

Technical UL/CSA

Maximum Operating Voltage UL/CSA	277 V AC
----------------------------------	----------

Material Compliance

RoHS Information	9AKK106713A5602
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20211115
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	e8229506-bdcb-47ec-b10f-6ae72c1a19bf Italy
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental

Ambient Air Temperature	Operation -25 ... 55 °C Storage -40 ... 70 °C
Degree of Protection	Terminals IP20 Housing IP40
Pollution Degree	2
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	Refer to RoHS

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	200 g
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.235 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5602
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK107991A6127
--------------------------	-----------------

Mounting Type	DIN-Rail
Mounting Position	Any

Popular Downloads

Data Sheet, Technical Information	9AKK107991A8329
-----------------------------------	-----------------

External Classifications and Standards

ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
UNSPSC	39121601
eClass	V11.0 : 27142201
IDEA Granular Category Code (IGCC)	4875 >> Residual current circuit breaker (RCCB)
Object Classification Code Standards	F IEC/EN 61008 UL 1053

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200912R0001	Auxiliary Contact	S2C-H6R	2	piece
2CDS200922R0001	Signal/Auxiliary Contact	S2C-S/H6R	2	piece
2CDS200946R0001	Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0003	Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200946R0002	Auxiliary Contact	S2C-H6-20R	1	piece
2CSS200911R0005	Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0007	Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0002	Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0008	Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0004	Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0006	Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0001	Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0010	Undervoltage Release	S2C-UA 230 DC	1	piece
2CSS200911R0009	Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0003	Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200910R0005	Overvoltage Release	S2C-OVP1	1	piece
2CSS200993R0005	Overvoltage Release	S2C-OVP2	1	piece
2CSF200989R0005	Auto-reclosing unit with autotest	F2C-ARH - T100	1	piece
2CSF201998R0034	Autoreclosing unit	F3C-AR24	1	piece
2CSF202998R0034	Autoreclosing unit	F3C-AR230	1	piece
2CSF203998R0034	Autoreclosing unit	F3C-AR230 D	1	piece
2CSS201998R0033	Motor Operating Device	S3C-MOD24	1	piece
2CSS202998R0033	Motor Operating Device	S3C-MOD230	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs



360°

