



 PRODUCT-DETAILS

F204 A S-125/0.3

Residual Current Circuit Breaker - 4P - Type A - 300 mA - 125 A



General Information

Extended Product Type	F204 A S-125/0.3
Product ID	2CSF204201R3950
EAN	8012542968207
Catalog Description	Residual Current Circuit Breaker - 4P - Type A - 300 mA - 125 A
Long Description	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.

Technical

Type of Residual Current	Type A
Test Voltage (Ut)	100-250 V
Maximum Surge Current	5 kA
Leakage Current Type	A
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Number of Poles	4P
Number of Modular Spacings per DIN Rail	4
Operating Characteristic	Selective

Position of Neutral Terminals	Right
Tightening Torque	2.8 N·m
Accessory Type	Signal/Auxiliary contact Motor operating device
Options Provided	None
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm ² Rigid 35 ... 35 mm ² Flexible 35 ... 35 mm ²
Rated Cross-Section	4 - Multi-Wired 0...25 mm ² 1 - Solid-Core 35...35 mm ²
Wire Stripping Length	12 mm
Terminal Type	Screw Terminals

Electrical

Rated Voltage (U_r)	230/400 V
Rated Operational Voltage	230 / 400 V AC
Rated Insulation Voltage (U_i)	500 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Input Voltage Type	AC
Rated Current (I_n)	125 A
Rated Residual Current	300 mA
Rated Conditional Short-Circuit Current (I_{nc})	10 kA
Frequency (f)	50/60 Hz
Rated Frequency (f)	50 Hz
Power Loss	at Rated Operating Conditions per Pole 11.2 W Total 33.6 W

Material Compliance

RoHS Information	9AKK106713A5606
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20211115
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	941b7388-e5f6-48ed-bf9e-6d5653c1c989 Italy
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental

Ambient Air Temperature	Operation -25 ... 40 °C Storage -40 ... 70 °C
Degree of Protection	IP2X
Pollution Degree	2
Environmental Information	Refer to RoHS

Dimensions

Width in Number of Modular Spacings	4
Product Net Width	72 mm
Product Net Height	85 mm
Product Net Depth / Length	69.5 mm
Product Net Weight	500 g
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.545 kg
E-Number (Norway)	1630590

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5606
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK107991A6132 9AKK107991A0963
Mounting Type	DIN-Rail
Mounting Position	Any

Popular Downloads

Data Sheet, Technical Information	9AKK107991A8329
-----------------------------------	-----------------

External Classifications and Standards

ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
eClass	V11.0 : 27142201
IDEA Granular Category Code (IGCC)	4875 >> Residual current circuit breaker (RCCB)
Object Classification Code	F
Standards	IEC/EN 61008

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CSF200922R0001	Signal/Auxiliary Contact	F2-125A-B-S/H	1	piece
2CSF200997R1214	Motor operating device	F2-125A-24V-CM4	1	piece
2CSF200997R1205	Motor operating device	F2-125A-230V-CM4	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs



360°