



PRODUCT-DETAILS

ISL-C 440

Insulation monitor



General Information

Extended Product Type	ISL-C 440
Product ID	2CSM545000R1500
EAN	8012542942900
Catalog Description	Insulation monitor
Long Description	ISL-C 440 is an insulation monitoring device for ac circuits

Technical

Model Number	Basic device
Delay Time (T)	Release 0...4 second [unit of time]
Options Provided	AC network

Electrical

Rated Operational Voltage	380 ... 415 V AC
Rated Control Supply	(50 Hz) 230...230 V

Voltage (Us)	(60 Hz) 230...230 V
Power Loss	at Rated Operating Conditions per Pole 4 W

Material Compliance

RoHS Information	9AKK108467A8682
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20231022
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental

Environmental Information	See RoHS Information
---------------------------	----------------------

Dimensions

Product Net Width	90 mm
Product Net Height	105 mm
Product Net Depth / Length	58 mm
Product Net Weight	270 g

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.3 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK108467A8682
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK108469A0620
	9AKK108469A0973

Popular Downloads

Data Sheet, Technical Information	9AKK108469A0611
-----------------------------------	-----------------

External Classifications and Standards

ETIM 9	EC001449 - Device for monitoring of safety-related circuits
--------	---

eClass

V11.0 : 27371819

Object Classification
Code

F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Industrial Insulation
Monitoring Devices

