

Sub-base VABS-S7-BE-B-N14-VDE1

Part number: 4727328

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|--------------------------------|--|
| Mounting position | Any |
| Pilot air supply | Internal |
| Operating pressure | 0.2 MPa ... 0.8 MPa |
| Operating pressure | 2 bar ... 8 bar |
| Flow rate Kv pressurisation | 2.2 m ³ /h |
| Flow rate Kv exhaust | 8.6 m ³ /h |
| Explosion protection | Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |
| Operating medium | Compressed air to ISO 8573-1:2010 [-:::] |
| Corrosion resistance class CRC | 4 - Very high corrosion stress |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Degree of protection | IP65 |
| Product weight | 250 g |
| Type of mounting | With through-hole |
| Pneumatic connection, port 1 | 1/4 NPT |
| Pneumatic connection, port 2 | VDI/VDE 3845 (NAMUR) |
| Pneumatic connection, port 3 | 1/4 NPT |
| Note on materials | RoHS compliant |
| Material sub-base | Ematal coated aluminium |
| Material seals | NBR |