

Linear/swivel clamp CLR-32-20-R-P-A-B-K11-R8

Part number: 535490

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Total stroke | 38 mm |
| Piston diameter | 32 mm |
| Piston rod thread | M8 |
| Swivel angle | 90 deg +/- 2 deg |
| Clamping stroke | 20 mm |
| Cushioning | Elastic cushioning rings/plates at both ends |
| Mounting position | Any |
| Design | Piston Piston rod Cylinder barrel |
| Position detection | Via proximity switch |
| Swivel direction | right |
| Symbol | 00991217 |
| Variants | Weld spatter protection Dust protection |
| Operating pressure | 2 bar ... 10 bar |
| Mode of operation | Double-acting |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Ambient temperature | -10 °C ... 80 °C |
| Effective clamping force at 0.2 MPa (2 bar, 29 psi) | 111 N |
| Effective clamping force at 0.4 MPa (4 bar, 58 psi) | 216 N |
| Effective clamping force at 0.6 MPa (6 bar, 87 psi) | 313 N |
| Max. tightening torque Clamping finger screw | 24 Nm |
| Theoretical clamping force at 0.6 MPa (6 bar, 87 psi) | 362 N |
| Product weight | 785 g |
| Type of mounting | With through-hole With female thread With accessories |
| Pneumatic connection | G1/8 |
| Material wiper | PPS |
| Material collar screws | Steel Galvanised |
| Material cover | Wrought aluminium alloy coated |

| Feature | Value |
|--------------------------|--------------------------------------------|
| Material seals | NBR TPE-U(PU) |
| Material housing | Smooth-anodised |
| Material piston rod | coated High-alloy stainless steel |
| Material cylinder barrel | Wrought aluminium alloy Smooth-anodised |