


Colour sensor SOEC-RT-Q50-PS-S-7L

Part number: 538236

FESTO



[PDF General operating condition](#)

Data sheet

Feature	Value
Design	Block design
Conforms to standard	EN 60947-5-2
Symbol	00991617
Approval	RCM c UL us - Listed (Oil)
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
Note on materials	RoHS compliant
Measured variable	Position
Measuring principle	Optoelectronic
Measurement method	Colour sensor
Type of light	White
Max. light spot	Ø 4 mm at a sensing range of 22 mm
Operating distance	12 mm ... 32 mm
Ambient temperature	-10 °C ... 55 °C
Switching output	PNP
Switching element function	Light switching
Max. switching frequency	500 Hz
Max. output current	100 mA
Voltage drop	≤2.4 V
Short circuit current rating	Pulsed
Operational voltage range DC	10 V ... 30 V
Residual ripple	10%
No-load supply current	40 mA
Reverse polarity protection	For all electrical connections
Electrical connection	M12x1 Plug
Size	50x50x17 mm
Type of mounting	With through-hole
Product weight	38 g
Material housing	ABS
Ready status indication	Green LED
Switching status indication	LED
Setting options	Teach-in Teach-in via electrical connection

Feature	Value
Setting range lower limit	12 mm
Setting range upper limit	32 mm
Ambient temperature with moving cable	-5 °C ... 55 °C
Degree of protection	IP67
Corrosion resistance class CRC	4 - Very high corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L