


Valve terminal VTSA-MP

Part number: 539215

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Electrical control	AP interface IO-Link® Multi-pin
Terminal type	44
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Ambient temperature	-5 °C ... 50 °C
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 90%
Degree of protection	IP65 NEMA 4
Corrosion resistance class CRC	0 - No corrosion stress
Operating pressure	-0.09 MPa ... 1 MPa
Operating pressure	-0.9 bar ... 10 bar
Pilot pressure	0.3 MPa ... 1 MPa
Pilot pressure	3 bar ... 10 bar
Operating pressure for valve terminal with internal pilot air supply	0.3 MPa ... 1 MPa
Operating pressure for valve terminal with internal pilot air supply	3 bar ... 10 bar
LABS (PWIS) conformity	VDMA24364-B1/B2-L
CE mark (see declaration of conformity)	To EU EMC Directive To EU Explosion Protection Directive (ATEX) To EU Low Voltage Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions To UK regulations for electrical equipment
KC mark	KC-EMV
Approval	BIA C-Tick c UL us - Recognised (Oil)
Explosion protection	Zone 2 (ATEX)
ATEX category gas	II 3G
Explosion ignition protection type for gas	Ex nA IIC T3 X Gc
Explosion ambient temperature	-5°C ≤ Ta ≤ +50°C
Certificate issuing authority	UL E322346
Note on materials	RoHS compliant
Valve terminal structure	Modular, valve sizes can be mixed
Max. number of valve positions	32

Feature	Value
Max. number of pressure zones	32
Type of actuation	Electrical
Valve function	5/3-way, port 2 pressurised, 4 exhausted
Design	Piston gate valve
Valve size	26 mm
Pilot air supply	External Internal
Max. standard nominal flow rate	550 l/min at 18 mm 1100 l/min at 26 mm 1300 l/min at 42 mm 2900 l/min at 52 mm 4000 l/min at 65 mm
Suitability for vacuum	Yes
Exhaust-air function	Via throttle plate
pneumatic working port	G1/8 G1/4 G3/8 G1/2 QS-6 QS-8 QS-10 QS-12 QS-14 QS-16
Signal status display	LED
Nominal operating voltage DC	24 V
Permissible voltage fluctuations	+/-10%