

Control block CPX-CM-HPP

Part number: 562214

FESTO



 General operating condition

Data sheet

| Feature | Value |
|--|---|
| Ambient temperature | -5 °C ... 50 °C |
| Product weight | 140 g |
| CE mark (see declaration of conformity) | To EU Low Voltage Directive |
| Degree of protection | IP65 IP67 |
| Storage temperature | -20 °C ... 70 °C |
| Note on materials | RoHS compliant |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Power failure bridging | 10 ms |
| Total number of axes | 4 |
| Dimensions (W x L x H) | 50 mm x 107 mm x 55 mm |
| Control-Interface | CAN bus |
| Field bus interface | 1x socket M9, 5-pin |
| Device-specific diagnostics | Channel-oriented and module-oriented diagnostics Undervoltage/short circuit of modules Diagnostics memory |
| Configuration support | MMI handheld terminal |
| Parameterisation | Forcing of channels System parameters |
| Baud rate | 1 Mbit/s |
| Operational voltage range DC | 18 V ... 30 V |
| Nominal operating voltage DC | 24 V |
| Protocol | FHPP |
| Intern power consumption nominal operating voltage | Typ. 80 mA |
| Max. address volume, outputs | 32 Byte |
| Max. address volume, inputs | 32 Byte |
| LED display, product-specific | Error PL: Load supply |
| Material housing | Makrolon® |