

Plug socket with cable NEBV-H1G2-KN-0.5-N-LE2

Part number: 566654

FESTO



 General operating condition

Data sheet

| Feature | Value |
|--|--------------------------------------|
| Cable designation | Without inscription label holder |
| Mounting position | Any |
| Product weight | 4 g |
| Electrical connection 1, function | Field device side |
| Electrical connection 1, design | Square |
| Electrical connection 1, connection type | Socket |
| Electrical connection 1, cable outlet | Straight |
| Electrical connection 1, connector system | Plug pattern H |
| Electrical connection 1, number of connections/cores | 3 |
| Electrical connection 1, used connections/cores | 2 |
| Electrical connection 1, type of mounting | Snap-locking |
| Electrical connection 1, connection pattern | 00995622 |
| Electrical connection 2, function | Control side |
| Electrical connection 2, connection type | 2x single cores |
| Electrical connection 2, connector system | Open end |
| Electrical connection 2, number of connections/cores | 2 |
| Electrical connection 2, used connections/cores | 2 |
| Operational voltage range DC | 0 V ... 60 V |
| Current rating at 40° C | 3 A |
| Cable length | 0.5 m |
| Cable characteristic | Standard |
| Cable diameter | 1.3 mm |
| Cable structure | 2 x 0.14 mm ² |
| Nominal cross section conductor | 0.14 mm ² |
| Wire ends | Cut off bluntly |
| Degree of protection | IP40 |
| Note on degree of protection | In mounted state |
| Ambient temperature | -5 °C ... 60 °C |
| CE mark (see declaration of conformity) | In accordance with EU RoHS Directive |
| UKCA marking (see declaration of conformity) | To UK RoHS instructions |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Note on materials | RoHS compliant |
| Material housing | POM |
| Housing colour | Black |
| Material electrical contact | Copper alloy Tin-plated |

| Feature | Value |
|----------------------------|-------|
| Material insulating sheath | PVC |