

Solenoid valve MHJ10-S-2,5-QS-6-HF

Part number: 567503

FESTO



 General operating condition

Data sheet

Feature	Value
Valve function	2/2-way, single solenoid, closed
Type of actuation	Electrical
Construction width	10 mm
Standard nominal flow rate (standardised to DIN 1343)	160 l/min
pneumatic working port	QS-6
Operating voltage	24 V DC
Operating pressure	0.05 MPa ... 0.6 MPa
Operating pressure	0.5 bar ... 6 bar
Operating pressure	7.25 psi ... 87 psi
Design	Poppet valve without spring return
Type of reset	Pneumatic spring
Degree of protection	IP55
Approval	RCM
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
Grid dimension	10.5 mm
Operating conditions to DIN VDE 0580	S3 50% 20 min. with individual valve S3 25% 20 min. with block mount
Note on operation	Do not operate without flow.
Sealing principle	Hard
Mounting position	Any
Manual override	None
Type of piloting	Direct
Flow direction	Non-reversible
Symbol	00992259
Reverse polarity protection	For operating voltage
Additional functions	Safety shut-off
b value	0.36
C value	0.66 l/sbar
Max. switching frequency	500 Hz
Switching time on 0.4 MPa (4 bar, 58 psi) and 24 V in new condition	1.2 ms
Switching time off 0.4 MPa (4 bar, 58 psi) and 24 V in new condition	0.6 ms
Switching time on 0.05 MPa (0.5 bar, 7.25 psi) and 24 V in new condition	1 ms
Switching time off 0.05 MPa (0.5 bar, 7.25 psi) and 24 V in new condition	0.8 ms
Switching time on 0.6 MPa (6 bar, 87 psi) and 24 V in new condition	1.3 ms

Feature	Value
Switching time off 0.6 MPa (6 bar, 87 psi) and 24 V in new condition	0.6 ms
Tolerance switching time off	+15%/-25%
Tolerance switching time on	+/-15 %
Operational voltage range DC	21.6 V ... 26.4 V
Input resistance	34 kOhm
Characteristic coil data	24 V DC: low-current phase 3.2 W, high-current phase 14.5 W
Trigger signal voltage range DC	3 V ... 30 V
Note on input current	Linear rise 0.09-0.44 mA with a trigger signal of 3-15 V 0.44-15.44 mA with a trigger signal of 15-30 V
Permissible voltage fluctuations	+/-10%
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation not possible
Restrictions for environmental and media temperature	As a function of switching frequency (see graph)
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Storage temperature	-20 °C ... 50 °C
Permissible solenoid surface temperature	120 °C
Media temperature	-5 °C ... 60 °C
Ambient temperature	-5 °C ... 60 °C
Product weight	85 g
Electrical connection	3-core Cable
Cable length	2.5 m
Type of mounting	Either: Inline installation With through-hole
Pneumatic connection, port 1	QS-6
Pneumatic connection, port 2	QS-6
Note on materials	RoHS compliant
Material seals	HNBR
Material housing	Reinforced PA Reinforced PPS
Material cable sheath	PUR
Material screws	Steel