

6ES7660-7CE08-3BD5

No picture available

SIMATIC PCS 7 Industrial Workstation IPC547G (rack PC, 19", 4 U), interfaces: 2x Gbit Ethernet (RJ45); 1x DVI-D; 2x Display Port V1.2 1x COM; 2x PS/2; audio; 2x USB 3.0 on the front, 4x USB 3.0 & 4x USB 2.0 on the rear side; 1x USB 2.0 internal; 7 slots: 5X PCI Express, 2x PCI; temperature and fan monitoring, watchdog, card retainer; Core I5-6500 (4C/4T, 3.2(3.6) GHz), 6 MB cache); MB (Chipset C236) - OS Client 1x1 TB HDD in removable frame, on front; 4 GB DDR4 SDRAM (1x 4 GB), single channel; Without additional system bus Communication card PCS 7 V9.0 SP3 pre-installed Windows 10 IoT Enterprise 2015 LTSB, 64 bit, MUI (en, de, fr, it, es, cn) Enclosure blue chromated, DVD+-RW (slim), Multi monitor 4 screens (combined, onboard interfaces (2 x DP) + Dual Head PCIE X16 card (2 x DP)), incl. 1xDP according to DVI-D adapter cable, incl. 1xDual DVI-I adapter for dual head PCIE X16 card 2x 100/240V AC redundant Industrial power supply unit, Power supply cable Europe

Notes

This product is a Spare Part, please visit the Spares & Service section for more information
If you need assistance please contact our local Siemens office

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6ES7660-7CE08-3BD5
Product Description	SIMATIC PCS 7 Industrial Workstation IPC547G (rack PC, 19", 4 U), interfaces: 2x Gbit Ethernet (RJ45); 1x DVI-D; 2x Display Port V1.2 1x COM; 2x PS/2; audio; 2x USB 3.0 on the front, 4x USB 3.0 & 4x USB 2.0 on the rear side; 1x USB 2.0 internal; 7 slots: 5X PCI Express, 2x PCI; temperature and fan monitoring, watchdog, card retainer; Core I5-6500 (4C/4T, 3.2(3.6) GHz), 6 MB cache); MB (Chipset C236) - OS Client 1x1 TB HDD in removable frame, on front; 4 GB DDR4 SDRAM (1x 4 GB), single channel; Without additional system bus Communication card PCS 7 V9.0 SP3 pre-installed Windows 10 IoT Enterprise 2015 LTSB, 64 bit, MUI (en, de, fr, it, es, cn) Enclosure blue chromated, DVD+-RW (slim), Multi monitor 4 screens (combined, onboard interfaces (2 x DP) + Dual Head PCIE X16 card (2 x DP)), incl. 1xDP according to DVI-D adapter cable, incl. 1xDual DVI-I adapter for dual head PCIE X16 card 2x 100/240V AC redundant Industrial power supply unit, Power supply cable Europe
Product family	Not available
Product Lifecycle (PLM)	PM410:Product cancellation
PLM Effective Date	Product is cancelled since: 01.10.2023
Notes	This product is a Spare Part, please visit the Spares & Service section for more information If you need assistance please contact our local Siemens office

Price data

Region Specific PriceGroup / Headquarter Price Group	S50 / 2L2
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	ECCN : 5A992 / AL : N
Estimated dispatch time (Working Days)	On request
Net Weight (kg)	15,000 Kg
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	84715000
LKZ_FDB/ CatalogID	STPCS7
Product Group	4519
Group Code	R1TP
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Given
Product class	B: return restricted, please contact your Siemens partner/contact
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Not available
--	---------------