

product type designation



Power Supply SCALANCE PS924 PoE

SCALANCE PS924 PoE power supply for power over Ethernet, input: 24 V DC output: 54 V DC/1.6 A NEC Class 2.

| | |
|--|---|
| type of current supply | Input: DC 24 V, Output: DC 54 V / 1.6 A, NEC CLASS 2 |
| suitability for use | Power supply for PoE |
| electrical data / input | |
| voltage curve / at input | DC |
| supply voltage / rated value | 24 V |
| supply voltage / rated value | 19.2 ... 28.8 V |
| type of voltage / of the supply voltage | DC |
| consumed current / at rated supply voltage / maximum | 4.1 A |
| design of input / wide range input | No |
| buffering time / for rated value of the output current / in the event of power failure / minimum | 5 ms |
| current limitation / of inrush current / at 25 °C / maximum | 10 A |
| fuse protection type / at input | Fuse T 15A soldered |
| electrical data / output | |
| voltage curve / at output | Controlled, isolated DC voltage, adjustable from 48 V to 54 V |
| output voltage | |
| • at DC / rated value | 54 V |
| display version / for normal operation | LED green for DC ok |
| behavior of the output voltage / when switching on | Overshoot of $U_a < 2\%$ |
| startup delay time / maximum | 1.5 s |
| voltage increase time / of the output voltage / maximum | 15 ms |
| output current | |
| • rated value | 1.6 A |
| • rated range | 0 ... 1.8 A |
| supplied active power / typical | 86 W |
| product feature / parallel switching of channels | No |
| number of parallel-switched equipment resources / for increasing the power | 0 |
| efficiency in percent | 86 % |
| power loss [W] | 14 W |
| electrical data / closed-loop control | |
| relative overall tolerance / of the voltage | 1 % |
| residual ripple / maximum | 0.05 V |
| voltage peak / maximum | 0.2 V |
| relative control precision / of the output voltage | |
| • on slow fluctuation of input voltage | 0.2 % |
| • on slow fluctuation of ohm loading | 0.5 % |
| • load step of resistive load 50/100/50 % / typical | 0.5 % |
| • with rapid fluctuation of the input voltage by +/- 15% / typical | 0.3 % |

| | |
|--|---|
| setting time | |
| • load step 50 to 100% / typical | 0.5 ms |
| • load step 100 to 50% / typical | 0.5 ms |
| electrical data / protection and monitoring | |
| design of the overvoltage protection / at output | < 60 V |
| response value current limitation / typical | 1.7 A |
| property of the output / short-circuit proof | Yes |
| design of short-circuit protection | Electronic shutdown, automatic restart |
| electrical data / safety | |
| galvanic isolation / between input and output | Yes |
| galvanic isolation | Safety extra-low output voltage U _{out} acc. to EN 60950-1 |
| operating resource protection class | Class III |
| leakage current | |
| • maximum | 3.5 mA |
| • typical | 0 mA |
| interfaces | |
| number of electrical connections | |
| • for power supply | 3 |
| • for signaling contact | 2 |
| type of electrical connection | |
| • for signaling contact | Screw terminal 0.5 - 2.5 mm ² |
| • at input | FE / + / - screw-type terminal 0,5 - 2,5 mm ² |
| • at output | 2x + / 2x - , screw-type terminal 0.5 - 2.5 mm ² |
| signal inputs/outputs | |
| product component / signaling contact | Yes |
| relay design | Normal open contact (N/O) |
| operating voltage / of the signaling contacts | |
| • at DC / rated value | 24 V |
| • at DC / maximum | 60 V |
| operational current / of the signaling contacts | |
| • at DC / maximum | 0.3 A |
| • at DC / at 30 V / maximum | 0.3 A |
| design, dimensions and weights | |
| width | 483 mm |
| height | 43.6 mm |
| depth | 150 mm |
| net weight | 0.5 kg |
| product feature / of the enclosure / housing can be lined up | Yes |
| fastening method | |
| • 19-inch installation | No |
| • wall mounting | No |
| • 35 mm top hat DIN rail mounting | Yes |
| • S7-300 rail mounting | No |
| ambient conditions | |
| ambient temperature | |
| • during operation | -40 ... +70 °C |
| • during storage | -40 ... +85 °C |
| • during transport | -40 ... +85 °C |
| • note | Convection |
| relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| environmental category / according to IEC 60721 | Climate class 3K3, without condensation |
| protection class IP | IP20 |
| standards, specifications, approvals | |
| standard | |
| • for safety / from CSA and UL | cULus listed (UL508, CSA C22.2 No. 107.1) |
| • for emitted interference | EN 61000-6-4: 2007 |
| • for interference immunity | EN 61000-6-2 |
| certificate of suitability | EN 61000-6-4: 2007 |
| • CE marking | Yes |
| • C-Tick | Yes |

| | |
|---|-----|
| reference code | TCB |
| <ul style="list-style-type: none"> • according to IEC 81346-2:2019 | |

standards, specifications, approvals / Environmental Product Declaration

| | |
|--|--|
| Environmental Product Declaration | Yes |
| Global Warming Potential [CO2 eq] | |
| <ul style="list-style-type: none"> • total • during manufacturing • during operation • after end of life | 595.15 kg 62.11 kg 532.64 kg 0.4 kg |

further information / internet links

| | |
|---|---|
| internet link | |
| <ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to web page: SiePortal • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support | https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com |

security information

| | |
|----------------------|---|
| security information | <p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p> |
|----------------------|---|

Approvals / Certificates

| General Product Approval | | | Environment | | |
|---|---|---|---|------------------------------|---|
|  |  |  |  | Confirmation |  |
| EG-Konf. | CCC | | RCM | | |

last modified:

9/25/2024 