

6GT2600-0AB10



Transponder MDS D160 for RF200/RF300 ISO/MOBY D heat resistant up to +175 ° ISO 15693 Chip type, NXP ICODE SLI, 112 byte user memory; 16x 3 mm (DxH); Minimum order quantity 100 units.	
List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6GT2600-0AB10
Product Description	Transponder MDS D160 for RF200/RF300 ISO/MOBY D heat resistant up to +175 ° ISO 15693 Chip type, NXP ICODE SLI, 112 byte user memory; 16x 3 mm (DxH); Minimum order quantity 100 units.
Product family	Not available
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	57T / 57T
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : EAR99H
Estimated dispatch time (Working Days)	1 Day/Days
Net Weight (kg)	0,001 Kg
Packaging Dimension	54,00 x 86,00 x 0,30
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Minimum order quantity	100

Additional Product Information

EAN	4011209681255
UPC	040892693959
Commodity Code	85235200
LKZ_FDB/ CatalogID	ID10.M
Product Group	4096
Group Code	R322
Country of origin	Malaysia
Compliance with the substance restrictions according to RoHS directive	Since: 01.07.2006
Product class	A: Standard product which is a stock item could be returned within the returns guidelines/period.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	1200	27-28-04-02
eClass	1400	27-28-04-02
eClass	600	27-28-04-01
eClass	710	27-28-04-01
eClass	800	27-28-04-01
eClass	900	27-28-04-02
eClass	910	27-28-04-02
ETIM	700	EC002996
ETIM	800	EC002996
ETIM	900	EC002996
IDEA	400	6645
UNSPSC	1500	43-21-17-10