

6GT2600-3AA10



Transponder MDS D339 for RF200/RF300 ISO/MOBY D heat resistant up to +220 °C ISO 15693, chip type INFINEON SRF 55V10P, 992-byte user memory; 85x 15 mm (DxH); minimum order quantity 10 units.

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	6GT2600-3AA10
Product Description	Transponder MDS D339 for RF200/RF300 ISO/MOBY D heat resistant up to +220 °C ISO 15693, chip type INFINEON SRF 55V10P, 992-byte user memory; 85x 15 mm (DxH); minimum order quantity 10 units.
Product family	Not available
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	57T / 57T
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	1 Day/Days
Net Weight (kg)	0,050 Kg
Packaging Dimension	15,00 x 85,00 x 85,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Minimum order quantity	10

Additional Product Information

EAN	4042948601723
UPC	887621412159
Commodity Code	85235200
LKZ_FDB/ CatalogID	ID10.M
Product Group	4096
Group Code	R322
Country of origin	Germany
Compliance with the substance restrictions according to RoHS directive	Since: 01.03.2003
Product class	A: Standard product which is a stock item could be returned within the returns guidelines/period.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

	Version	Classification
eClass	1200	27-28-04-02
eClass	1400	27-28-04-02
eClass	600	27-28-04-01
eClass	710	27-28-04-01
eClass	800	27-28-04-01
eClass	900	27-28-04-02
eClass	910	27-28-04-02
ETIM	700	EC002996
ETIM	800	EC002996
ETIM	900	EC002996
IDEA	400	6645
UNSPSC	1500	43-21-17-10