

Electric cylinder ESBF-...-32- -

Part number: 8022569

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Size	32
Stroke	30 mm ... 800 mm
Piston rod thread	M10x1.25
Spindle diameter	12 mm
Torsional backlash at piston rod +/-	0.25 deg
Based on standard	ISO 15552
Mounting position	Any
Type of motor	Stepper motor Servo motor
Position detection	Via proximity switch
Design	Electric cylinder with ball screw Electric cylinder with lead screw spindle
Symbol	00991941
Variants	Metals with copper, zinc or nickel by mass as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.
Protection against torque/guide	With plain-bearing guide
Duty cycle	100%
Corrosion resistance class CRC	2 - Moderate corrosion stress 3 - high corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Cleanroom suitability, measured according to ISO 14644-14	Class 7 according to ISO 14644-1
Storage temperature	-20 °C ... 60 °C
Suitable for use with food	See supplementary material information
Relative air humidity	0 - 95%
Degree of protection	IP40 IP65
Ambient temperature	0 °C ... 60 °C
Max. radial force at drive shaft	115 N
Max. feed force Fx	1000 N
Frictional torque independent of load	0.1 Nm
Type of mounting	With female thread Or accessories
Interface code, actuator	D32
Note on materials	RoHS compliant

Feature	Value
Material cover	Wrought aluminium alloy, smooth anodised
Material piston rod	High-alloy stainless steel
Material screws	Galvanised steel
Material ball screw nut	Bearing steel
Material spindle	Bearing steel
Material cylinder barrel	Smooth-anodised wrought aluminium alloy