


# Solenoid valve VSVA-B-P53C-Z-A2-1T1L

Part number: 8033492

FESTO



[General operating condition](#)

## Data sheet

| Feature   | Value  |
|---|--|
| Valve function  | 5/3-way, closed  |
| Type of actuation                                     | Electrical   |
| Construction width                                    | 18 mm  |
| Standard nominal flow rate (standardised to DIN 1343) | 450 l/min  |
| pneumatic working port                                | Sub-base size 18 mm to ISO 15407-1<br>Sub-base size 02 to VDMA 24563<br>G1/8 |
| Operating voltage                                     | 24 V DC  |
| Operating pressure                                    | -0.09 MPa ... 1 MPa  |
| Operating pressure                                    | -0.9 bar ... 10 bar  |
| Design  | Piston gate valve  |
| Approval  | c UL us - Recognised (Oil)   |
| Degree of protection                                  | IP65<br>NEMA 4   |
| Exhaust-air function                                  | Can be throttled<br>Via throttle plate<br>Via individual sub-base            |
| Sealing principle                                     | Soft   |
| Mounting position                                     | Any  |
| Manual override                                       | Concealed  |
| Type of piloting                                      | Piloted  |
| Pilot air supply                                      | External<br>Internal   |
| Flow direction  | Any  |
| Symbol  | 00992992   |
| lap   | Overlap  |
| Signal status display                                 | LED  |
| Pilot pressure  | 0.3 MPa ... 1 MPa  |
| Pilot pressure  | 3 bar ... 10 bar   |
| Flow rate of valve                                    | 700 l/min  |
| Flow rate of valve on individual sub-base             | 550 l/min  |
| Valve flow rate, pneumatically linked, flow optimized | 650 l/min  |
| Flow rate of pneumatically interlinked valve          | 450 l/min  |
| Switching time off                                    | 44 ms  |
| Switching time on                                     | 15 ms  |
| Duty cycle  | 100%   |
| Max. positive test pulse with 0 signal                | 1500 µs  |

| Feature                                | Value  |
|--|--|
| Max. negative test pulse with 1 signal | 800 µs   |
| Max. current consumption               | 72 mA  |
| Nominal operating voltage DC           | 24 V   |
| Characteristic coil data               | 24 V DC: 1.6 W   |
| Immunity to surge                      | 2.5 kV   |
| Pollution degree                       | 3  |
| Permissible voltage fluctuations       | +/-10%   |
| Operating medium                       | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Note on operating and pilot medium     | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance                   | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6           |
| Shock resistance                       | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                          |
| Corrosion resistance class CRC         | 0 - No corrosion stress  |
| LABS (PWIS) conformity                 | VDMA24364-B1/B2-L  |
| Relative air humidity                  | 0 - 90%  |
| Pilot medium                           | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Ambient temperature                    | -5 °C ... 50 °C  |
| Product weight                         | 191 g  |
| Electrical connection                  | Plug-in<br>To ISO 15407-2  |
| Type of mounting                       | On sub-base  |
| Pilot air port 12/14                   | Sub-base size 18 mm to ISO 15407-2   |
| Pilot exhaust port 82/84               | Ducted<br>Not ducted as per standard<br>Either:  |
| Pneumatic connection, port 1           | Sub-base size 18 mm to ISO 15407-2   |
| Pneumatic connection, port 2           | Sub-base size 18 mm to ISO 15407-2   |
| Pneumatic connection, port 3           | Sub-base size 18 mm to ISO 15407-2   |
| Pneumatic connection, port 4           | Sub-base size 18 mm to ISO 15407-2   |
| Pneumatic connection, port 5           | Sub-base size 18 mm to ISO 15407-2   |
| Note on materials                      | RoHS compliant   |
| Material seals                         | Fluoro rubber<br>HNBR<br>NBR   |
| Material housing                       | Die-cast aluminium<br>Process automation   |
| Material screws                        | Galvanised steel   |