


# Signal converter SCDN-2V-EC4-PNLK-L1

Part number: 8035555

FESTO



General operating condition

## Data sheet

Feature	Value
Symbol	00995687
Approval	RCM c UL us - Listed (Oil)
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
Certificate issuing authority	UL E322346
Note on materials	RoHS compliant
Measured variable	Voltage
analog input	0 - 10 V
Ambient temperature	0 °C ... 50 °C
Typical sampling interval	1 ms
Accuracy in ± % FS	0.5 %FS
Repetition accuracy in ± %FS	0.2 %FS
Switching output	2 x PNP or 2 x NPN, switchable
Switching function	Freely programmable
Switching element function	NC or NO, switchable
Max. output current	100 mA
Short circuit current rating	Yes
Protocol	IO-Link®
IO-Link, Protocol version	Device V 1.1
IO-Link, Profile	Smart sensor profile
IO-Link, Function classes	Binary data channel (BDC) Process data variable (PDV) Identification Diagnostics Teach channel
IO-Link, communication mode	COM2 (38.4 kBaud)
IO-Link, SIO-Mode support	Yes
IO-Link, Port class	A
IO-Link, Process data length OUT	0 bytes
IO-Link, Process data length IN	5 bytes
IO-Link, Process data content IN	14 bit PDV (InA measurement) 14 bit PDV (measured value InB) 2 bit BDC (measured value monitoring)
IO-Link, Min. cycle time	5 ms

Feature	Value
IO-Link, Data storage required	500 Byte
Operational voltage range DC	15 V ... 30 V
Reverse polarity protection	For all electrical connections
Electrical connection 1, connection type	Plug
Electrical connection 1, connector system	Plug pattern L1J
Electrical connection 1, number of connections/cores	4
Electrical connection 1, connection pattern	00995428
Electrical connection 2, connection type	2x socket
Electrical connection 2, connector system	Connection pattern EC
Electrical connection 2, number of connections/cores	4
Electrical connection 2, connection pattern	00995750
Type of mounting	Via wall/surface bracket
Product weight	23 g
Material housing	Reinforced PA
Display type	Illuminated LCD, multi-colour
Setting options	IO-Link® Teach-in Via display and buttons
Protection against tampering	IO-Link® PIN code
Degree of protection	IP40
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L