


Valve terminal VTUG-EX

Part number: 8060699

FESTO



 General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Electrical control	Fieldbus I-Port IO-Link® Multi-pin
Electrical I/O system	No
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Pilot medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Media temperature	-5 °C ... 60 °C
Ambient temperature	-5 °C ... 60 °C
Storage temperature	-10 °C ... 60 °C
Degree of protection	IP20 IP65
Corrosion resistance class CRC	2 - Moderate corrosion stress
Vibration resistance	Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27
Operating pressure	-0.09 MPa ... 1 MPa
Operating pressure	-0.9 bar ... 10 bar
Pilot pressure	0.15 MPa ... 0.8 MPa
Pilot pressure	1.5 bar ... 8 bar
Operating pressure for valve terminal with internal pilot air supply	1.5 bar ... 8 bar
LABS (PWIS) conformity	VDMA24364-B2-L
CE mark (see declaration of conformity)	To EU EMC Directive To EU Explosion Protection Directive (ATEX) In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
Approval	RCM c UL us - Recognised (Oil)
Explosion protection	Zone 2 (ATEX) Zone 2 (BR) Zone 22 (ATEX) Zone 22 (BR)
ATEX category gas	II 3G
ATEX category dust	II 3D
Explosion protection certification outside the EU	EPL Dc (BR) EPL Gc (BR)

Feature	Value
Explosion ignition protection type for gas	Class I, Zone 2, AEx ec IIC Gc (US) Ex ec IIC Gc (CA) Ex ec IIC T4 Gc
Explosion ignition protection type for dust	Class II, Zone 22, AEx tc IIIC T135 Dc (US) Ex tc IIIC T135 Dc (CA) Ex tc IIIC T135°C Dc
Explosion ambient temperature	-5°C ≤ Ta ≤ +50°C -5°C ≤ Ta ≤ +60°C
Certificate issuing authority	DNV 23.0350 X/00 IBExU16ATEXB021 X IECEX IBE 17.0003 X IECEX IBE 19.0018 X UL E198674 UL MH19482
Note on materials	RoHS compliant
Material seals	HNBR NBR
Valve terminal structure	Fixed grid
Max. number of valve positions	24
Max. number of pressure zones	13
Type of actuation	Electrical
Valve function	2x3/2 closed monostable 2x3/2 open monostable 2x3/2-way, open/closed, monostable 3/2-way, single solenoid, closed 3/2-way, single solenoid, open 5/2-way, double solenoid 5/2-way, single solenoid 5/3-way, pressurised 5/3 exhausted 5/3-way, closed
Design	Piston gate valve
Sealing principle	Soft
Type of piloting	Piloted
Valve size	18 mm
Pilot air supply	External Internal
Max. standard nominal flow rate	330 l/min at 10 mm 630 l/min at 14 mm 1200 l/min at 18 mm
Standard nominal flow rate (standardised to DIN 1343)	130 l/min ... 1150 l/min
Suitability for vacuum	Yes
Exhaust-air function	Can be throttled
pneumatic working port	M5 M7 G1/8 G1/4 QS-3 QS-4 QS-6 QS-8 QS-10 QS-5/32 QS-1/8 QS-3/16 QS-1/4 QS-5/16 QS-3/8
Pneumatic connection, port 1	QS-16 QS-1/4 QS-5/16 QS-3/8 QS-1/2
Pilot air port 12/14	G1/8

Feature	Value
Signal status display	LED
Nominal operating voltage DC	24 V
Permissible voltage fluctuations	+/-10% +/-25%
Nominal pick-up current per solenoid coil	47 mA to 20 ms
Nominal current with current reduction	15.5 mA after 20 ms