

# Analogue input module CPX-AP-I-4AI-U-I-RTD-M12

Part number: 8086606

FESTO



 General operating condition

## Data sheet

Feature	Value
Dimensions (W x L x H)	30 mm x 170 mm x 35 mm
Type of mounting	On DIN rail via accessories With through-hole
Product weight	166 g
Ambient temperature	-20 °C ... 60 °C
Storage temperature	-40 °C ... 70 °C
Relative air humidity	5 - 95% Non-condensing
Degree of protection	IP65 IP67
Note on degree of protection	Unused connections sealed
Corrosion resistance class CRC	1 - Low corrosion stress
Max. cable length	30 m inputs 50 m system communication
LABS (PWIS) conformity	VDMA24364-B2-L
Cleanroom suitability, measured according to ISO 14644-14	Element installed statically, no meaningful evaluation possible according to ISO 14644-1
CE mark (see declaration of conformity)	To EU EMC Directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC
KC mark	KC-EMV
Approval	RCM c UL us - Listed (Oil)
Certificate issuing authority	UL E239998
Note on materials	RoHS compliant
Material housing	Makrolon® Nickel-plated die-cast zinc
Material seals	NBR
Material o-ring	Fluoro rubber
Diagnostics via LED	Diagnostics per module Status per channel
Diagnostics per internal communication	Wire breakage Module error Short circuit/overload in sensor supply Parameter error Parameterisation error Overload analogue inputs Upper limit value violated Underflow/overflow Lower limit value not observed
Communication interface, function	System communication XF10 IN / XF20 OUT

Feature	Value
Communication interface, connection type	2x socket
Communication interface, connection technology	M8x1, D-coded according to EN 61076-2-114
Communication interface, number of pins/cores	4
Communication interface, protocol	AP
Communication interface, screened	Yes
Power supply, function	Incoming electronics/sensors and load
Power supply, connection type	Plug
power supply, connection system	M8x1, A-coded to EN 61076-2-104
Power supply, number of pins/wires	4
Power transmission, function	Outgoing electronics/sensors and load
Power transmission, connection type	Socket
Power transmission, connection technology	M8x1, A-coded to EN 61076-2-104
Power transmission, number of pins/wires	4
Note regarding operating voltage	SELV/PELV fixed power supplies required Note the voltage drop
Nominal DC operating voltage, electronics/sensors	24 V
Permissible voltage fluctuations for electronics/sensors	±25%
Max. power supply	2 x 4 A (external fuse required)
Intrinsic current consumption at nominal operating voltage for electronics/sensors	Typically 38 mA
Power failure bridging	10 ms
Reverse polarity protection	Yes
Electrical connection input, function	Analogue input
Electrical connection input, connection type	4x socket
Electrical connection input, connector system	M12x1, A-coded to EN 61076-2-101
Electrical connection input, note on connector system	To achieve compliance with the technical specifications, the opposite side must be screened and designed with gold contact surfaces.
Electrical connection input, number of connections/cores	5
Number of inputs	4
Fuse protection of inputs (short circuit)	Internal electronic fuse per module
Max. residual current of inputs per module	1 A
Electrical isolation of inputs between channels	No
Electrical isolation of inputs between channel – internal communication	Yes
Measured variable	Voltage Current Temperature Resistor
Note on the measured variable	Temperature: PT100 and NI100 supported
Data format	15 bits + prefix Linear scaling
analog input	-10 - 10 V -5 - 5 V 0 - 10 V 1 - 5 V 0 - 20 mA 4 - 20 mA 0 - 500 Ohm
Repetition accuracy	±0.025% at 25°C
Basic error limit at 25 °C	±0.1% for voltage ±0.1 % for voltage ±0.4% for temperature ±0.2 % for resistance
Operating error limit related to the ambient temperature range	±0.15% for voltage ±0.15% for current ±0.9 % for temperature ±0.35% for resistor