

# Plug screw NETC-P-M20-PBK-T26-EX4-E

Part number: 8151589

FESTO



 [General operating condition](#)

## Data sheet

| Feature   | Value   |
|---|---|
| Ambient temperature                               | -40 °C ... 75 °C  |
| Degree of protection                              | IP66<br>IP68  |
| Note on degree of protection                      | IP68 at 5 bar for 30 minutes  |
| ATEX category gas                                 | II 2G   |
| ATEX category dust                                | II 2D   |
| Explosion ignition protection type for gas        | Ex eb IIC Gb  |
| Explosion ignition protection type for dust       | Ex tb IIIC Db   |
| Explosion ambient temperature                     | -40°C ≤ Ta ≤ +75°C  |
| Explosion protection certification outside the EU | EPL Db (IEC-EX)<br>EPL Gb (IECEX)   |
| CE mark (see declaration of conformity)           | To EU Explosion Protection Directive (ATEX)<br>In accordance with EU RoHS Directive |
| Size  | M20x1.5   |
| Colour  | Black   |
| Material cable gland                              | Process automation  |
| Material seals                                    | EPDM  |
| Product weight                                    | 5 g   |
| Size of pack                                      | 1   |
| LABS (PWIS) conformity                            | VDMA24364 zone III  |
| Note on materials                                 | RoHS compliant  |