


# Pilot valve

## VOFX-LT-M32C-MY-G18-SG18-1C3-EX4-M

FESTO

Part number: 8178212



[General operating condition](#)

### Data sheet

Feature	Value
Valve function	3/2-way, single solenoid, closed
Type of actuation	Electrical
Construction width	22 mm
Standard nominal flow rate (standardised to DIN 1343)	50 l/min
pneumatic working port	G1/8
Operating voltage	24 V DC
Operating pressure	-0.09 MPa ... 0.8 MPa
Operating pressure	-0.9 bar ... 8 bar
Operating pressure	-13.05 psi ... 116 psi
Design	Directly actuated poppet valve
Type of reset	Mechanical spring
Degree of protection	IP65
CE mark (see declaration of conformity)	To EU Explosion Protection Directive (ATEX) In accordance with EU RoHS Directive
Explosion protection certification outside the EU	EPL Db (BR) EPL Db (CN) EPL Db (IEC-EX) EPL Gb (BR)
Certificate issuing authority	IECEx PTB 15.0016X PTB 14 ATEX 2027 X
ATEX category gas	II 2G
ATEX category dust	II 2D
Explosion ignition protection type for gas	Ex mb IIC T6 Gb
Explosion ignition protection type for dust	Ex mb tb IIIC T80°C Db
Explosion ambient temperature	-20°C ≤ Ta ≤ +50°C
Nominal size	1.3 mm
Exhaust-air function	Can be throttled
Sealing principle	Soft
Mounting position	Any
Manual override	Detenting
Type of piloting	Direct
Pilot air supply	Internal
Flow direction	Non-reversible
Symbol	00991135
Duty cycle	100%
Insulation material class	F
Characteristic coil data	24 V DC: 2.6 W

Feature	Value
Permissible voltage fluctuations	+/-10%
Explosion protection	Zone 1 (ATEX) Zone 1 (BR) Zone 2 (ATEX) Zone 21 (ATEX) Zone 21 (BR) Zone 21 (CN) Zone 21 (IEC-EX) Zone 22 (ATEX)
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Ambient temperature	-10 °C ... 50 °C
Product weight	418 g
Electrical connection	Cable
Cable length	3 m
Pneumatic connection, port 1	G1/8
Pneumatic connection, port 2	G1/8
Pneumatic connection, port 3	M5
Note on materials	RoHS compliant
Material seals	NBR
Material housing	Process automation
Material solenoid coil	Copper